

|HF-R1200 14小头圆弧抛光机|陶瓷加工机械

产品名称	HF-R1200 14小头圆弧抛光机 陶瓷加工机械
公司名称	佛山市顺德区鸿陶进机电有限公司
价格	面议
规格参数	加工定制:是 类型:抛光设备 品牌:鸿发/HongFa
公司地址	广东佛山市顺德区北滘镇三乐路马龙大道
联系电话	0757-28866874 13702260041

产品详情

hf-r1200圆弧抛光机

hf-r1200 arc polishing machine

hf-r圆弧抛光机是我厂的传统产品，它可以把任何级别的抛光砖和石材进行弧面加工而成为靓丽的梯级砖和地角线。该机生产过程全自动运作，操作简单方便，可随意调节生产线的速度，可随意调节所加工的圆弧面的大小。亦可抛光45°角度。选用鸿发圆弧抛光机，祝你企业腾飞。

hf-r arc polishing machine is our traditional superior product,its suitable for polishing the edge of ceramic,marble,granite to make beautiful skirting and step tile.

it also can make and polishing 45° tile edge.simple operation,full automatic and high capacity.

型号	description	单位/unit	hf-r10	hf-r14	hf-r20
输送带数量	qty. of conveying belt	pcs	1	1	1
抛光磨头数量	number of polishing heads	pcs	10	14	20
抛光磨头直径	dia of polishing heads	mm	100	100	100
倒角磨边轮数量	qty.of squaring and chamfering wheel	pcs	5	6	6
倒角磨边轮直径	dia of squaring chamfering wheel	mm	150	150	150
开槽数量	qty. of grooving wheel	pcs	2-4	2-4	2-4
开槽刀片直径	dia of the grooving wheel	mm	150	150	150
气动倒边角磨头数量	numbers of down chamfering head	pcs	1	1	1
气动倒边角磨头直径	dia of down chamfering head	mm	100	100	100
吹干出风口	qty of drying line	pcs	2	2	2
工作宽度	working width	mm	80-1200	80-1200	80-1200

抛光速度	polishing speed	m/min	3-4	4-6	8-10
加工砖厚度	working thickness	mm	6-30	6-30	6-30
总功率	total power	kw	29	33	39
耗气量	air consumption	l/min	50	55	55
外型尺寸	dimension	m × m × m	6.5 × 2.2 × 1.8	7.9*2.2*1.8	8.6*2.2*1.8
重量	weight	kg	4000	5300	6300

本产品的加工定制是是，类型是抛光设备，品牌是鸿发/HongFa，型号是HF-R1200，用途是加工梯级砖和地脚线，45度抛光，加工能力是全自动运作，操作简单方便，产品别名是圆弧抛光机，规格是7.9*2.2*1.8

.8