

rxh-14-b	ct-	120	1.1	20	20	2800	± 2	48	2430 × 1200	2375
rxh-27-b	ct-	240	2.2	40	40	5200	± 2	96	2430 × 2200	2433
rxh-41-b	ct-	360	3	60	80	8000	± 2	144	3430 × 2200	2620
rxh-54-b	ct-	480	4	80	100	9800	± 2	192	4460 × 2200	2620
rxh-5-c	ct-c-o	25	0.45	5	5	3450	± 2	16	1130 × 1100	1750
rxh-7-c	ct-c- a	50	0.45	10	10	3450	± 2	24	1400 × 1200	2000
rxh-14-c	ct-c-	120	0.45	18	20	3450	± 2	48	2300 × 1200	2000
rxh-27-c	ct-c-	240	0.9	36	40	6900	± 2	96	2300 × 2200	2000
rxh-27a-c	ct-c- a	240	0.9	36	40	6900	± 2	96	4460 × 1200	2290
rxh-41-c	ct-c-	360	1.35	54	80	10350	± 2	144	3430 × 2200	2000
rxh-42a-c	ct-c- a	360	1.35	54	80	10350	± 2	144	2300 × 3200	2000
rxh-54-c	ct-c-	480	1.8	72	100	13800	± 2	192	4460 × 2200	2290
rxh-25-a	高效高温远红外灭菌烘箱 功率配套按温度要求进行								1200 × 1000	1600

适应物料适用于制药、化工、食品、农副产品、水产品、轻工、重工等行业物料及产品的加热固化、干燥脱水。如原料药、生药、中药饮片、浸膏、粉剂、颗粒、冲剂、水丸、包装瓶、颜料染料、脱水蔬菜、瓜果干、香肠、塑料树脂、电器元件、烘漆等。