

扫地车用马达

产品名称	扫地车用马达
公司名称	济宁力耐通液压机械有限公司
价格	1.00/台
规格参数	品牌:力耐通 型号:LM
公司地址	山东省济宁市高新开发区内
联系电话	0537-2031618 13792343699

产品详情

LMS?????????

??????LMS??

????

LMS????????????????????

- ????????,???????
- ????????????????
- ????????, ?????????
- ????????????????????
- ????????????????????

LMS motor is a disc valve type gerolor motor.

Characteristic features?

- Advanced design in disc distribution flow, which can provide improved performance at low speed.
- Advanced design of shaft seal, which can bear higher pressure.
- Advanced distribution mechanism design, which has the automatic compensation function.
- Double-rolling bearing design, which permit higher radial loads.
- A variety of connection types of flange; Rabbet:, output shaft and oil port.

????? Main Specification

- 1.????????????????????.
- 2.????????????????.
- 3.????????????????10%.
- 4.??68#??????37-73cSt???ISO18/13
- 5.????80°
- 6.????????????40% ???1h.
- 7.??????10MPa??????5MPa????????.

- 1. Intermittent means the entrance of the maximum pressure; continuous working pressure means the differential pressure
- 2. Motor should not work under the highest pressure and the maximum speed
- 3. The running time should not exceed 10% under intermittent working conditions

4. Recommending N68 anti-wear hydraulic oil, viscosity 37-73cSt, cleanliness ISO18/13.
5. The Maximum working temperature is 80 °
6. One hour running time under 40% of maximum working pressure is recommended before full capacity working.
7. The maximum allowable back pressure is 10MPa, but the recommended back pressure should not exceed 5MPa. a leaking pipes is needed when exceeding

LMS ????????----??? Dimension and Mounting data

LMS????? ?????----??? Shaft

LMS????????----?? Port

LMS??????? Ordering Information

LMS Ordering Information

LMS???????????

