

花粉包装机 SUN-420粉剂包装设备

产品名称	花粉包装机 SUN-420粉剂包装设备
公司名称	佛山市晟奇奥机械有限公司
价格	125000.00/台
规格参数	薄膜宽度:420mm 制袋长度:80-300 制袋宽度:50-200
公司地址	广东佛山市南海区丹灶镇罗行社区校北大街3号
联系电话	86 0757 86604198 18038857967

产品详情

420立式粉剂包装机

技术特点：

- 1 . 采用彩色触摸屏和稳定可靠的双轴高精度输出的plc控制、制袋、计量、充填、封合、打码、切袋一次性完成。
- 2 . 气路控制和电路控制电箱独立分离，噪音小，电路更稳定。
- 3 . 采用双皮带伺服拉膜：拉膜阻力少，包装袋成型好，更美观，皮带不易磨损。
- 4 . 采用伺服控制，实现高精度定位，尺寸准确。
- 5 . 采用外置式放膜机构，包装膜安装更简单、更容易。
- 6 . 包装袋的偏差调整只需在触摸屏上调整即可，操作简单。
- 7 . 整机采用封闭式机构，有效防止粉尘进入机器内部。

technical characteristics

1. plc control with stable & reliable biaxial high accuracy output and color touch screen, bag-making, measuring, filling, printing,cutting , finished in one operation.

2. separate circuit boxes for pneumatic control and power control. noise is low, and the circuit is more stable.
3. film-pulling with servo motor double belt: less pulling resistance, bag is formed in good shape with better appearance, belt is resistant to be worn-out.
4. double servo control, high precision orientation, size more nicely.
5. external film releasing mechanism: simpler and easier installation of packing film.
6. adjustment of bag deviation just needed to be controled by the touch screen. operation is very simple .
7. close down type mechanism , defending powder into inside of machine.

技术要点：

1 . 本机采用伺服电机控制 , 螺杆计量方式 , 精确度可达 $\pm 1\%$ 。

2 . 调整产品重量无需任何工具。

technical characteristics:

1 . the machine adopt servo motor control, screw measuring, precision $\pm 1\%$.

2 . adjustment product weight without any tools.

适用包装范围：

适合包装粉剂：奶粉，豆粉，面粉，等一切粉类。

application

suitable packing powder : milk powder , bean powder ,etc.

技术参数 (technical parameters) :

机型 (type)	sun-420
制袋长度(bag length)	80-300mm(l)
制袋宽度(bag width)	50-200mm(w)
薄膜宽度(max width of roll film)	420mm
包装速度(packing speed)	5-70bags/min

计量范围(measuring range)	150-1200ml
气压(air consumption)	0.65mpa
耗气量(gas consumption)	0.3m3/min
电压 (power voltage)	220v
功率 (power)	2.2kw
外型尺寸 (dimension)	(l)1320mm × (w)950mm × (h)1360mm
机器重量 (deadweight of machine)	540kg