

双向阀 代尔 东风商用车及改装车

产品名称	双向阀 代尔 东风商用车及改装车
公司名称	十堰代尔汽车零部件有限公司
价格	12.00/个
规格参数	品牌:代尔 型号:3526N-010 适用车型:东风商用车及改装车
公司地址	汽配城A区三栋002号
联系电话	0719-8312201 13387157799

产品详情

品牌	代尔	型号	3526N-010
适用车型	东风商用车及改装车		
	产品名称：双向阀 3526n-010		

主要用途(application) :

双向阀是两个独立的气源气压交替向一个方向流动，并且总是气压高的一方起作用，交替时压差达到0.2bar。此阀主要用于辅助制动，它的作用能使辅助制动/驻车制动同主车制动独立开，以防止制动力叠加。它主要用于弹簧制动气室，当辅助/驻车制动管路断裂时，能通过外部的空气能源来释放弹簧制动气室。 the double check valve id used to alternate the direction of air flow when tow separate means of charging a line are available .the higher pressure is effective at any given time ,and the charge - over takes place at a pressure difference of 0.2bar as a maximum value . in the main , the valve is used for the auxiliary brake for the purpose of separating the normal service brake form the auxiliary /parking brake to prevent the addition of braking forces. the valve is mainly used as a pneumatic released valve for the spring brake cylinder of the auxiliary brake in the eventuality of a rupture of the indirect brake line ,in which case it would be necessary to release the spring brake cylinder through an external source of air.

技术参数(technical features) :

- 1、最大工作气压 850kpa
 - 2、工作介质 压缩空气
 - 3、温度范围 -40 ~+80
- 1.max.operating pressure 850kpa 2.permmissible medium air 3.temperature range -40 ~+80

适用车型(applicable type of vehicles) :

eq1141g等各种气制动的车型