

型号	流量q (l/s)	压力p (mpa)	转速n (r/min)	效率 (%)	功率n (kw)	必须汽蚀余量(n _{psh})r (m)
xbd1.8/5-50w	5	0.18	1450	65	2.2	3.2
xbd2.7/5-50w	5	0.27	1450	65	3	3.2
xbd3.6/5-50w	5	0.36	1450	65	4	3.2
xbd4.5/5-50w	5	0.45	1450	65	5.5	3.2
xbd5.4/5-50w	5	0.54	1450	65	5.5	3.2
xbd6.3/5-50w	5	0.63	1450	65	7.5	3.2
xbd7.2/5-50w	5	0.72	1450	65	7.5	3.2
xbd8.1/5-50w	5	0.81	1450	65	7.5	3.2
xbd2.3/10-75w	10	0.23	1450	68	5.5	3.0
xbd3.4/10-75w	10	0.34	1450	68	7.5	3.0
xbd4.6/10-75w	10	0.46	1450	68	11	3.0
xbd5.5/10-75w	10	0.55	1450	68	11	3.0
xbd6.9/10-75w	10	0.69	1450	68	15	3.0
xbd8.0/10-75w	10	0.80	1450	68	15	3.0
xbd9.2/10-75w	10	0.92	1450	68	18.5	3.0
xbd10.3/10-75w	10	1.03	1450	68	18.5	3.0
xbd2.9/20-100w	20	0.29	1450	72	11	3.5
xbd4.3/20-100w	20	0.43	1450	72	15	3.5
w						
xbd5.8/20-100w	20	0.58	1450	72	22	3.5
xbd7.2/20-100w	20	0.72	1450	72	30	3.5
xbd8.6/20-100w	20	0.86	1450	72	30	3.5
xbd10.1/20-100w	20	1.01	1450	72	37	3.5
w						
xbd11.5/20-100w	20	1.15	1450	72	45	3.5
w						
xbd13.0/20-100w	20	1.30	1450	72	45	3.5
w						
xbd4.2/25-125w	25	0.42	1450	73	22	3.5
xbd6.3/25-125w	25	0.63	1450	73	30	3.5
xbd8.4/25-125w	25	0.84	1450	73	45	3.5
xbd10.5/25-125w	25	1.05	1450	73	55	3.5
w						
xbd12.6/25-125w	25	1.26	1450	73	75	3.5
w						
xbd14.7/25-125w	25	1.47	1450	73	75	3.5
w						
xbd16.8/25-125w	25	1.68	1450	73	90	3.5
w						
xbd18.9/25-125w	25	1.89	1450	73	90	3.5
w						
xbd5.8/45-150w	45	0.58	1450	76	45	3.0
xbd8.7/45-150w	45	0.87	1450	76	75	3.0
xbd11.6/45-150w	45	1.16	1450	76	90	3.0
w						
xbd14.5/45-150w	45	1.45	1450	76	110	3.0
w						
xbd17.4/45-150w	45	1.74	1450	76	135	3.0
w						

xbd20.3/45-150 W	45	2.03	1450	76	155	3.0
xbd23.2/45-150 W	45	2.32	1450	76	180	3.0
xbd26.1/45-150 W	45	2.61	1450	76	180	3.0

本产品的品牌是一环，型号是XBD-W，压力是0.18-2.61（Mpa），材质是铸铁，泵轴位置是卧式，叶轮吸入方式是单吸式，驱动方式是电动，用途是消防泵，流量是5-45（m³/h），功率是2.2-180kw，转速是1450，必需汽蚀余量是3.2-3.0，是否提供加工定制是是