



型号 规格	公称 传动比 i0	外形及中心高							轴伸							地脚尺寸							质量 kg
		l	b	h	h0	r	d	d	l1	l2	t1	b1	t2	b2	l1	l2	l3	l0	b1	d1	h		
ngw 11	2.8-4.5	530	28	295	125	12	35	50	55	85	38.5	10	55	16	215	16	25	105	220	m16	20	53	
	5-12.5	477	0		0	5	30		50		33	8				5		57				50	
ngw 21	2.8-4.5	604	30	325	140	14	40	60	70	105	43.5	12	65.5	18	245	18	30	115.	235	m20	25	80	
	5-12.5	535	5		0	0	35		55		38.5	10				5		5				73	
ngw 31	2.8-4.5	632	35	365	160	16	45	70	70	105	49	14	76	20	260	20	30	125	270	m20	25	100	
	5-12.5	569	0		0	0	40		70		43.5	12				0		62				98	
ngw 41	2.8-4.5	734	38	425.	180	18	50	80	85	105	55	16	87	24	290	23	30	156	320	m24	30	147	
	5-12.5	634	0	5	0	0	45		70		50	14				0		72				128	
ngw 51	2.8-4.5	845	42	463.	200	20	55	90	85	115	60	16	97	24	310	25	30	196.	360	m24	35	213	
	5-12.5	729	0	5	0	0	50		85		55	16				0		5				193	
ngw 61	2.8-4.5	886	47	524	225	22	60	100	105	125	65.5	18	108	28	360	29	35	202.	405	m30	40	289	
			5		0	5										0		5					



本产品的加工定制是是，类别是行星减速机，齿轮类型是圆柱齿轮减速机，安装形式是卧式，布局形式是同轴式，齿面硬度是硬齿面，用途是减速机，品牌是荆泰，型号是NGW11-2.8，输入转速是1500（rpm），额定功率是11（kw），输出转速范围是120-535（rpm），使用范围是工业，级数是单级，减速比是2.8，规格是NGW11