YF-用于处理含油水过滤选核桃壳滤水材料-

产品名称	YF-用于处理含油水过滤选核桃壳滤水材料-
公司名称	上海易芙环保科技有限公司
价格	2000.00/个
规格参数	滤料类型:其他 适用对象:水 用途:水过滤
公司地址	上海市奉贤区奉村路258号1幢E98室
联系电话	86 0131 22614700 13122614700

产品详情

yf-用于处理含油水过滤选核桃壳滤水材料

核桃壳滤料是采用优质的山核桃壳作原料,经过破碎、抛光、蒸洗、药物处理,两次筛选加工而成的一种水处理滤料。核桃壳滤料具有硬度高、耐磨损、抗压性好,抗压力为23.4kgf,化学性能稳定,不在酸碱中溶解、吸附截污能力强,吸附率为27—50%,亲水性好,抗油浸等优点。核桃壳滤料由于本身的硬度，理想的比重、多孔和多面性，并经特殊的物理化学处理（将其色素、脂肪、油脂、电付离子去除干净），使它在水处理中具有较强的除油性能，除固体微粒，易反洗等优良性能。pecan shell of walnut shell filter material is made of high quality raw material, after crushing, polishing, steaming, washing, drug treatment, two filter processing and become a kind of water treatment filter material.walnut shell filter material has high hardness, good wear resistance, pressure resistance, resistance to pressure is 23.4 kgf, stable chemical performance, not in the acid and alkali dissolution, adsorption section carrying capacity is strong, the adsorption rate of 27-50%, good hydrophilicity, oil resistance, etc.walnut shell filter material due to the hardness of itself, the proportion of ideal, porous and multifaceted, and the special physical and chemical treatment, the pigment, fat, oil, electric ion removal clean), make it has strong oil removal in water treatment performance, in addition to the solid particles, easy backwashing and other excellent properties.

检测项目	测试数据	检测项目	测试数据
油去除率	90-95%	反洗强度	$25m^3/m^2 \cdot h$
悬浮物去除率	95-98%	水冲洗压力	0.32mpa
滤速	20-25m/h	维护方式	每年补充5-10%
密度	$1.25g/cm^3$	堆密度	$0.8g/cm^3$

广泛应用于油田、化工、制革等工业污水处理及城市给水排水工程，是各种过滤器最理想的水质净化过滤材料。widely used in oil field, chemical industry, leather and other industrial wastewater treatment and urban

water supply and drainage engineering, is the most ideal water purification filter material of various filters.

1、运输与装卸：产品在运输过程中，不得用铁钩拖拽，应防止与坚硬物质混装，不可强烈振动、磨擦、踩、砸，严禁抛掷，应轻装轻卸，以减少产品破碎，影响使用。2、储存：应储存于阴凉干燥处，防止内外包装袋破裂，防止受潮和吸附空气中其它物质，影响使用效果。严禁与有毒有害气体或易挥发物质混放，存放要远离污染源。1, transportation and loading and unloading: products in the transport process, not drag hook, should prevent mixed with the solid material, strong vibration, friction, hit, hit, forbid throwing should be lightly armed light discharge to reduce fragmentation, the impact of the use.2, storage: should be stored in a cool dry place, prevent the internal and external packaging bag rupture, prevent moisture and other substances in the absorption of air, the effect of the use of. it is strictly forbidden to mix with toxic and harmful gases or volatile substances, and keep away from pollution sources.

包装塑料编织袋包装，每袋25公斤。置于阴凉干燥处，不宜暴晒。packageplastic woven bag, 25 kg. store in a cool dry place, not exposure

由于产品规格种类多，价格不同，具体价格以客服经理当天报价为准。请您在购买前联系客服经理，我们会第一时间回复您！欢迎来电！due to the variety of products, the price is different, the specific price will be subject to customer service manager on the day of quotation.you before buying, please contact customer service manager, we will first time reply you!welcome to call!

上海易芙环保科技有限公司联系人：赵敏电话：13122614700qq:2650509224地址：中国上海奉贤区奉村路258号shanghai yifu environmental protection technology co., ltd.contact person: zhao minphone: 13122614700qq:2650509224address: no. 258,fengcun road fengxian district, shanghai, china

上海易芙环保科技有限公司是活性炭、椰壳炭、果壳炭、煤质炭、颗粒炭、柱状炭、聚丙烯酰胺、聚合氯化铝、各种滤料等产品专业生产加工的公司，拥有完整、科学的质量管理体系。上海易芙环保科技有限公司的诚信、实力和产品质量获得业界的认可。欢迎各界朋友莅临参观、指导和业务洽谈。 shanghai yifu environmental protection technology co., ltd. activated carbon, coconut shell charcoal, nut shell activated carbon, coal activated carbon, granular activated carbon, column shaped carbon, polyacrylamide, poly aluminum chloride, a variety of media and other products specialized production and processing companies, has a complete and scientific quality management system. shanghai yifu environmental protection science and technology limited company's good faith, strength and quality of products recognized by the industry. welcome all friends to visit, guidance and business negotiation.

本产品的滤料类型是其他，适用对象是水，用途是水过滤，性能是耐酸,耐碱,耐高温,防静电，类型是高效，品牌是其他，抗压力是23.4（kgf），密度是1.25（g/cm3），孔隙率是47（%），磨损率是1.5，硬度是3