

ISG立式管道增压循环离心泵14寸 欢乐泵业

产品名称	ISG立式管道增压循环离心泵14寸 欢乐泵业
公司名称	温岭市欢乐水泵风机厂
价格	面议
规格参数	品牌:金农 型号:GW管道泵 材质:铸铁
公司地址	温岭市大溪镇中岙张村村部
联系电话	6321782

产品详情

gw系列管道泵					
序号	型号	流量	扬程	功率	转速
		m3/h	m	kw	r/min
1	25-8-22-1.1	8	22	1.1	2900
2	32-12-15-1.1	12	15	1.1	
3	40-15-15-1.5	15	15	1.5	
4	40-15-30-2.2	15	30	2.2	
5	50-20-7-0.75	20	7	0.75	
6	50-10-10-0.75	10	10	0.75	
7	50-20-15-1.5	20	15	1.5	
8	50-15-25-2.2	15	25	2.2	
9	50-25-15-2.2	25	15	2.2	
10	50-18-30-3	18	30	3	
11	50-25-32-5.5	25	32	5.5	
12	50-20-40-7.5	20	40	7.5	
13	65-42-9-2.2	42	9	2.2	
14	65-25-15-2.2	25	15	2.2	
15	65-37-13-3	37	13	3	
16	65-27-15-3	27	15	3	
17	65-25-30-4	25	30	4	
18	65-30-40-7.5	30	40	7.5	
19	65-35-50-11	35	50	11	

20	65-35-60-15	35	60	15	
21	80-40-7-2.2	40	7	2.2	1450
22	80-50-10-3	50	10	3	2900
23	80-43-13-3	43	13	3	
24	80-40-15-4	40	15	4	
25	80-65-20-5.5	65	20	5.5	
26	80-65-25-7.5	65	25	7.5	
27	100-80-10-4	80	10	4	1450
28	100-110-10-5.5	110	10	5.5	
29	100-100-15-7.5	100	15	7.5	
30	100-80-20-7.5	80	20	7.5	
31	100-100-25-11	100	25	11	
32	100-100-30-15	100	30	15	
33	100-100-35-18.5	100	35	18.5	
34	125-100-15-11	100	15	11	
35	125-130-20-15	130	20	15	
36	150-145-9-7.5	145	9	7.5	
37	150-180-15-15	180	15	15	
38	150-180-20-18.5	180	20	18.5	
39	150-180-25-22	180	25	22	
40	150-130-30-22	130	30	22	
41	150-180-30-30	180	30	30	
42	150-200-30-37	200	30	37	
43	150-150-35-37	150	35	37	
1	200-300-7-11	300	7	11	980
2	200-400-7-15	400	7	15	
3	200-250-11-15	250	11	15	980
4	200-250-15-18.5	250	15	18.5	980
5	200-400-10-22	400	10	22	1450
6	200-300-15-22	300	15	22	
7	200-400-13-30	400	13	30	
8	200-250-22-30	250	22	30	
9	200-350-25-37	350	25	37	
10	200-400-25-45	400	25	45	
11	200-400-30-55	400	30	55	
12	250-600-9-30	600	9	30	980
13	250-600-12-37	600	12	37	1450
14	250-600-15-45	600	15	45	
15	250-600-20-55	600	20	55	
16	250-600-25-75	600	25	75	
17	300-800-12-45	800	12	45	980
18	300-500-15-45	500	15	45	
19	300-800-15-55	800	15	55	
20	300-600-20-55	600	20	55	
21	300-800-20-75	800	20	75	
22	300-950-20-90	950	20	90	

本产品的品牌是金农，型号是GW管道泵，材质是铸铁，性能是卫生，用途是管道泵,增压泵,屏蔽泵,其他，驱动方式是电动，输送介质是清水泵，泵轴位置是边立式，叶轮结构是敞开式叶轮，叶轮吸入方式是单吸式，流量是1000-1100（m³/h），扬程是10-36（m），电压是380（V），功率是55-160（kw），规格是350-1100-10-55,350-1300-12-75,350-1500-15-90,350-1200-18-90,350-1100-28-132,350-1000-36-160