

陶瓷纤维板 高铝型陶瓷纤维挡火板

产品名称	陶瓷纤维板 高铝型陶瓷纤维挡火板
公司名称	淄博同发耐火保温材料有限公司
价格	8000.00/公斤
规格参数	导热系数:1 () 耐火温度:1100-1600 () 耐压强度:10 (Mpa)
公司地址	淄博市周村区恒星路136号
联系电话	13864479009

产品详情

导热系数	1 ()	耐火温度	1100-1600 ()
耐压强度	10 (Mpa)	规格	20-60 (mm)

同发耐纤 窑炉首选

绝对保证自己生产自己加工，绝对不是皮包公司，经销商，原厂生产加工设计施工，为你省时省事省钱，产品绝对是阿里巴巴上性价比最高了产品，欢迎到厂实地参观考察。

如有需要请电话联系，绝对质优价廉~

一、产品说明:陶瓷纤维板采用散棉加无机粘合剂用湿法真空吸滤加压成形,并按不同型号经过高温锻烧处理,该产品同时具备低容重高强度的优良特性,,是一种多用途产品,可应用于炉衬热面抗火焰和高温气流直接冲击。二、特点:高温稳定低导热率低热容抗热震抗侵蚀易加工和切割性能精准的厚度与尺寸良好的抗火焰及气流冲刷安装使用方便三、产品应用:可应用于同时要求坚韧,自承重及隔热的领域,它具有有良好的抗机械破坏性能。领域包括:推板窑、钢包炉、钟罩窑、隧道窑、辊道窑、熔铝炉、热处理炉等绝热内衬和背衬;高温挡火板;窑车隔热;各种高温工业窑炉隔热。四、理化数据

i. product description:aluminosilicate fiberboard increase the use of casual cotton inorganic adhesive wet filter vacuum pressure forming, and different models through high-temperature calcination departmentthe rationale for the product at the same time with high-strength low-density fine features, is a multi-purpose products, lining can be applied to the

flame and heat resistant surface a direct impact on high-temperature airflow. second, characteristics: high temperature stability, low thermal conductivity, low heat capacity, thermal shock resistance, anti-erosion, easy processing and cutting performance, precise thickness and size, good anti-flame and air scour. the installation of easy-to-use. third, product applications: requirements can be applied at the same time tough, since the load-bearing areas and thermal insulation, it has a good performance against mechanical damage. areas include: push board kiln, ladle furnace, bell kiln, tunnel kiln, roller kiln, aluminum melting furnace, heat treatment furnace, such as insulation in lining and backing; high-temperature thermal block plate; kiln car insulation; a variety of high temperature industrial furnace insulation. fourth, physical and chemical data model: std-1000 hp-1260 ha-1420 hg-1600. classification temperature (°C) 1000 1260 1420 1600. bulk density (kg/m³) 160-250 160-250 160-250 160-250. re-burned linear shrinkage (%) <1.4 (800°C × 24hr) <1.3 (1000°C × 24hr) <1.5 (1150°C × 24hr) <2 (1500°C × 24hr). of science group into % al₂O₃ 37 42 30 65. sio₂ + al₂O₃ >96 99 88 >99. fe₂O₃ <1.0 0.2 0.2 -. zro₂ - - 8 -. product specifications (mm): the standard 600 × 400 × 20 ~ 50. 900 × 600 × 20 ~ 50.

型号		std1000	gp-1260	ha-1420	hg-1600
分类温度 (°C)		1000	1260	1420	1600
容重 (kg/m ³)		160-250	160-250	160-250	160-250
重烧线收缩 (%)		< 1.4(800°C × 24hr)	< 1.3(1000°C × 24hr)	< 1.5(1150°C × 24hr)	< 2(1500°C × 24hr)
化学组成%	al ₂ O ₃	37	42	30	65
	sio ₂ + al ₂ O ₃	>96	99	88	>99
	fe ₂ O ₃	<1.0	0.2	0.2	-
	zro ₂	-	-	8	-

产品规格 (mm) : 标准 600 × 400 × 20 ~ 50 900*600*20-50