

供水系统只需一套气压给水设备，大大节省资金的投入；平常自动运行供水主泵，不会因消防水泵长期闲置而火警发生时消防系统的正常运转。

设备用途	气压罐类型	附加功能	z: 消防专用型 i: 隔膜式 h: 双电源切换	g: 生活、消防共用型 ii: 补气式 c: 消防泵自动巡检	b: 消防稳压
------	-------	------	--------------------------------	--------------------------------------	---------

注：稳高压消防系统稳压罐为总容积；局部增压设施及保证10min消防水量的气压罐为有效水容积。

设备型号		消防水泵			稳压装置	
		流量l/s	扬程m	功率kw	稳压泵功率kw	气
xqz(g)4/5	0.150.300.45	5	33	4	1.5	
xqz(g)4/10-	0.150.300.45	10	39	7.5		容
xqz(g)4/15-	0.150.300.45	15	40	11		×
xqz(g)4/20-	0.150.300.45	20	40	15		:
xqz(g)4/25	0.150.300.45	25	44	22		00
						最
						m
xqz(g)6/30	0.150.300.45	30	40	22	2.2	
xqz(g)6/5	0.150.300.45	5	55	5.5		容
xqz(g)	0.150.300.45	10	52	11		×
xqz(g)6/15-	0.150.300.45	15	60	15		:
xqz(g)6/20-	0.150.300.45	20	60	22		00
xqz(g)6/25-	0.150.300.45	25	66	30		最
xqz(g)6/30-	0.150.300.45	30	60	30		m
xqz(g)6/40-	0.150.300.45	40	60	37	3	
xqz(g)6/50-	0.150.300.45	50	63	45		容
xqz(g)8/5-	0.150.300.45	5	77	7.5		×
xqz(g)8/10	0.150.300.45	10	78	15		:
xqz(g)8/15-	0.150.300.45	15	80	22		00
xqz(g)8/20-	0.150.300.45	20	80	30		最
						m
xqz(g)8/25-	0.150.300.45	25	88	37	3	
xqz(g)8/30-	0.150.300.45	30	80	37		容
xqz(g)8/40-	0.150.300.45	40	80	45		×
xqz(g)8/50-	0.150.300.45	50	84	75		:
xqz(g)10/5-	0.150.300.45	5	99	11		00
						最
						m
xqz(g)10/10-	0.150.300.45	10	91	22	4	
						容
						×

xqz(g)10/15-	0.150.300.45	15	100	30
xqz(g)10/20-	0.150.300.45	20	100	37
xqz(g)10/25-	0.150.300.45	25	88	37
xqz(g)10/30-	0.150.300.45	30	100	45
xqz(g)10/40-	0.150.300.45	40	100	55
xqz(g)10/50-	0.150.300.45	50	105	75
xqz(g)12/10-	0.150.300.45	10	117	22

4

性能参数表：（湖北申博泵业有限公司027-83266165）

序号	增压稳压设备型号	消防压力(mpa)p1	立式隔膜式气压罐				配用水泵 型号	运行压力 (mpa)	
			型号规格	工作压力 比 b	消防储水容积(l)				
					标定容积	实际容积			
1	zw(l)-1-x-7	0.10	xqg800 × 0.6	0.60	300	319	25lg3-10 × 4 n=1.5kw	p1=0.10 ps1=0.2 p1=0.23 ps2=0.3	
2	zw(l)-1-z-10	0.16	xqg800 × 0.6	0.80	150	159	25lg3-10 × 4 n=1.5kw	p1=0.16 ps1=0.2 p1=0.23 ps2=0.3	
3	zw(l)-1-x-10	0.16	xqg800 × 0.6	0.60	300	319	25lg3-10 × 5 n=1.5kw	p1=0.16 ps1=0.3 p1=0.33 ps2=0.4	
4	zw(l)-1-x-13	0.22	xqg1000 × 0.6	0.76	300	329	25lg3-10 × 4 n=1.5kw	p1=0.22 ps1=0.3 p1=0.32 ps2=0.4	
5	zw(l)-1-xz-10	0.16	xqg1000 × 0.6	0.65	450	480	25lg3-10 × 4 n=1.5kw	p1=0.16 ps1=0.3 p1=0.30 ps2=0.3	
6	zw(l)- -xz-13	0.22	xqg1000 × 0.6	0.67	450	452	25lg3-10 × 5 n=1.5kw	p1=0.22 ps1=0.4 p1=0.38 ps2=0.4	
7	zw(l)- -z-	a	0.22 -0.38	xqg800 × 0.6	0.80	150	159	25lg3-10 × 6 n=2.2kw	p1=0.38 ps1=0.5 p1=0.50 ps2=0.6
8		b	0.38 -0.50	xqg800 × 1.0	0.80	150	159	25lg3-10 × 8 n=2.2kw	p1=0.50 ps1=0.6 p1=0.65 ps2=0.7
9		c	0.50 -0.65	xqg1000 × 1.0	0.85	150	206	25lg3-10 × 9 n=2.2kw	p1=0.65 ps1=0.8 p1=0.78 ps2=0.8
10		d	0.65 -0.85	xqg1000 × 1.6	0.85	150	206	25lg3-10 × 11	p1=0.85 ps1=1.0

								n=3.0kw	p1=1.02 ps2=1.1
11		e	0.85-1.0	xqg1000 × 1.6	0.85	150	206	25lg3-10 × 13	p1=1.00 ps1=1.2
								n=4.0kw	p1=1.19 ps2=1.2
12	zw(l)- -x-	a	0.22-0.38	xqg800 × 0.6	0.78	300	302	25lg3-10 × 6	p1=0.38 ps1=0.5
								n=2.2kw	p1=0.50 ps2=0.6
13		b	0.38-0.50	xqg800 × 1.0	0.78	300	302	25lgw3-10 × 8	p1=0.50 ps1=0.6
								n=2.2kw	p1=0.65 ps2=0.7
14		c	0.50-0.65	xqg1000 × 1.0	0.78	300	302	25lg3-10 × 10	p1=0.65 ps1=0.8
								n=3.0kw	p1=0.86 ps2=0.9
15		d	0.65-0.85	xqg1200 × 1.6	0.85	300	355	25lg3-10 × 13	p1=0.85 ps1=1.0
								n=4.0kw	p1=1.02 ps2=1.1
16		e	0.85-1.0	xqg1200 × 1.6	0.85	300	355	25lg3-10 × 15	p1=1.00 ps1=1.2
								n=4.0kw	p1=1.19 ps2=1.2
17	zw(l)- -xz-	a	0.22-0.38	xqg1200 × 0.6	0.80	450	474	25lg3-10 × 6	p1=0.38 ps1=0.5
								n=2.2kw	p1=0.50 ps2=0.6
18		b	0.38-0.50	xqg1200 × 1.0	0.80	450	474	25lg3-10 × 8	p1=0.50 ps1=0.6
								n=2.2kw	p1=0.65 ps2=0.7
19		c	0.50-0.65	xqg1200 × 1.0	0.80	450	474	25lg3-10 × 10	p1=0.65 ps1=0.8
								n=3.0kw	p1=0.78 ps2=0.8
20		d	0.65-0.85	xqg1200 × 1.6	0.80	450	474	25lg3-10 × 12	p1=0.85 ps1=1.0
								n=4.0kw	p1=1.02 ps2=1.1
21		e	0.85-1.0	xqg1200 × 1.6	0.80	450	474	25lg3-10 × 14	p1=1.00 ps1=1.2
								n=4.0kw	p1=1.19 ps2=1.2

本产品的品牌是申博，型号是ZW(W)-I-Z-13，压力是0.4（Mpa），材质是铸铁，泵轴位置是边立式，叶轮吸入方式是单吸式，驱动方式是电动，性能是不阻塞,卫生,自动，用途是管道泵,消防泵，原理是离心泵，输送介质是清水泵，适用范围是消防管道增压稳压，流量是0.1（m3/h），扬程是44（m），叶轮结构是1，叶轮数目是1，工作压力是0.44，重量是580（kg），电压是380（V），规格是ZW（W），功率是2.2，转速是2950，效率是78