

RCB2沥青泵配1.1kw电机

产品名称	RCB2沥青泵配1.1kw电机
公司名称	河北远东泵业制造有限公司
价格	面议
规格参数	品牌:远东 型号:RCB2
公司地址	河北省泊头市道东街88号
联系电话	0317-8185077 13831765644

产品详情

用途	型号	公司名称
输送船用油泵	KCB55齿轮泵	上海外高桥造船有限公司
输送车辆齿轮油泵	KCB-18.3(2CY-1.1/14.5)	杭州橡胶集团有限公司
输送工业齿轮油泵	SNS1300R54E6.7W21三螺杆泵	中国百兴集团有限公司
输送军用齿轮油泵	KCB-55(2CY-3.3/0.33)	浙江桐昆集团股份有限公司
输送压缩机油泵	SNH660R54U12.1W2三螺杆泵	三角集团有限公司
输送冷冻机油泵	KCB-83.3(2CY-5/0.33)	华勤橡胶工业集团
输送汽轮机油泵	NYP50-LU-M1-W51高粘度泵	洛阳热电厂
输送成品油泵	KCB-300(2CY-18/0.36)	江苏新世纪造船股份有限公司
磨煤机螺杆泵	SNH660R54E6.7W1三螺杆泵	开滦能源化工股份有限公司
高粘度硅胶泵	NYP50-RL-T1-J-W21高粘度泵	贵州瓮福集团有限公司
输送801胶泵	NYP110-RU-T2-W51高粘度泵	玲珑集团股份有限公司
输送738胶泵	NYP50-RL-T1-J-W12高粘度泵	山东垦利石化有限责任公司
高粘度树脂泵	NYP110-RU-T2-W11高粘度泵	山东东明石化集团有限公司
喷胶输送泵	NYP220B-RU-T2-W11高粘度泵	深圳市金斯邦胶粘剂有限公司
喷胶泵	NYP-7-RU-M1-W51高粘度泵	上海把兄弟胶粘剂有限公司

船用气涡轮用滑油泵 稀油润滑系统泵	KCB-483.3(2CY-29/0.36) SPF40R54G10W21三螺杆泵	江苏扬子江船厂有限公司 云南煤化工集团有限公司
液压站磨煤机螺杆泵	SNS1300R42U12.1W21三螺杆泵	华能沁北电厂
水电厂磨煤机螺杆泵	SNS120R46U12.1W2三螺杆泵	北京大唐陡河电厂
高粘度树脂泵	NYP220B-RU-T1-W11高粘度泵	荣盛石化股份有限公司
输送洗涤原料泵	NYP-320B-LU-T1-J-W12高粘度泵	江苏金浦集团有限公司
输送表面活性剂泵	G35-1V-W112单螺杆泵	利华益集团股份有限公司
输送山梨醇泵	G50-2V-W101单螺杆泵	佳通轮胎（中国）有限公司
输送果葡糖浆泵	G105-2P-W101单螺杆泵	浙江传化集团有限公司

RCB沥青保温泵分为普通与铸钢两种材质，均带有保温夹套，保温泵适用于常温下有凝固性或结晶而通过加温并保持一定温度又容易流动且有润滑性的液体，以及高寒地区室外安装和工艺过程中需要保温的场合，泵开始工作时首先预热降低了泵的起动功率。适用于输送有腐蚀性或无腐蚀性、卫生条件要求较高的液体，输送介质不含固体颗粒，温度不高于350℃，粘度为5cSt——1500cSt的液体，如各种化工原料、灌装医药、食品、化妆品、农药、洗涤剂、印染、酿造、树脂、胶类等行业。该泵传动方式有电机直联和减速机两种，当液体粘度超过1500cSt时，应采用减速机传动。RCB asphalt heat pump can be divided into ordinary and cast steel material, with thermal insulation jacket, heat pump under applicable interesting coagulability and crystallization and by heating and maintain a certain temperature and easy flow and lubricity of liquid, in the process of the high altitude and outdoor installation process and need to heat preservation, pump starts to work when the first preheating reduced the starting power of the pump. Applicable to transport corrosive or non-corrosive, health conditions to demand higher liquid, medium not containing solid particles, the temperature is not higher than 350℃, the viscosity of liquid for 5 CST - 1500 CST, such as filling a variety of chemical raw materials, pharmaceutical, food, cosmetics, pesticide, detergent, printing and dyeing, brewing, resin, rubber and other industries. The pump drive way has two kinds of motor and deceleration machine, when more than 1500 CST liquid viscosity reducer drive should be adopted.

沥青保温泵的泵体设有空心夹层，并设有进出口法兰，可用于导热油、蒸气、热水、等媒体对输送的液体和泵进行加热保温及冷却该泵传动方式有电机直联和减速机两种，当液体粘度超过1500cSt时，应采用减速机传动。

Asphalt heat pump pump body has a hollow interlayer, with import and export of flange, can be used in the thermal oil, steam, hot water, such as the media for the transportation of liquid and pump heat insulation and cooling ways there are to the pump drive motor and deceleration machine two, when more than 1500 CST liquid viscosity reducer drive should be adopted.

沥青保温齿轮泵结构形式：Asphalt insulation gear pump structure:

泵体设有空心夹层，并设有进出口法兰，可用于导热油、蒸气、热水等媒体对输送的液体和泵进行加热保温及冷却。

Pump body has a hollow sandwich, with import and export of flange, can be used in the thermal oil, steam, hot water and other media for conveying liquid and heat insulation and cooling pump.

适用范围：Scope of application:

适用于输送无腐蚀性、不含固体颗粒、在常温下有凝固性的介质，尤其适用于高寒地区室外安装和工艺过程中介质需要保温的场合，介质温度可达250℃、粘度为5-1500cst。

Is applicable to transport non-corrosive, not containing solid particles, at room temperature with coagulability medium, especially in cold area outdoor media need to heat preservation in the process of installation and process, medium temperature can reach 250℃, the viscosity of 5 to 1500 CST.

用途说明：

为输送常温下变稠，凝固或结晶而维持一定温度又容易流动的介质而设计的，如沥青、石蜡、松香及性质类似的液体，温度不高于200℃。

Purpose:

For transport has thickened under normal temperature, solidification or crystallization and maintain a certain temperature and easy flow of medium, such as asphalt, paraffin wax, rosin and properties similar liquid, the temperature is not higher than 200℃.