

液体硫磺泵用RCB5保温齿轮泵

| | |
|------|--------------------------|
| 产品名称 | 液体硫磺泵用RCB5保温齿轮泵 |
| 公司名称 | 河北远东泵业制造有限公司 |
| 价格 | 面议 |
| 规格参数 | 品牌:远东 型号:RCB5 |
| 公司地址 | 河北省泊头市道东街88号 |
| 联系电话 | 0317-8185077 13831765644 |

产品详情

RCB-5/0.36流量:5m³/h,压力:0.36Mpa,吸入真空高度:3米,口径:40,配电机:Y100L-4

RCB保温齿轮泵可以输送的介质包括:沥青,乳化沥青,拼板胶,山梨醇,太古油,乳化油,油脂,椰子油,大豆油,高温润滑脂,按摩油,双氧乳,油浆,热熔胶,合成胶粘剂,聚氨酯密封胶,耐高温硅胶等.

沥青保温齿轮泵结构形式 : Asphalt insulation gear pump structure:

泵体设有空心夹层,并设有进出口法兰,可用于导热油、蒸气、热水等媒体对输送的液体和泵进行加热保温及冷却。 Pump body has a hollow sandwich, with import and export of flange, can be used in the thermal oil, steam, hot water and other media for conveying liquid and heat insulation and cooling pump.

适用范围 : Scope of application:

适用于输送无腐蚀性、不含固体颗粒、在常温下有凝固性的介质,尤其适用于高寒地区室外安装和工艺过程中介质需要保温的场合,介质温度可达250、粘度为5-1500cst。

Is applicable to transport non-corrosive, not containing solid particles, at room temperature with coagulability medium, especially in cold area outdoor media need to heat preservation in the process of installation and process, medium temperature can reach 250, the viscosity of 5 to 1500 CST.

用途说明 : Purpose:

为输送常温下变稠,凝固或结晶而维持一定温度又容易流动的介质而设计的,如沥青、石蜡、松香及性质类似的液体,温度不高于200。 For transport has thickened under normal temperature, solidification or crystallization and maintain a certain temperature and easy flow of medium, such as asphalt, paraffin wax, rosin and properties similar liquid, the temperature is not higher than 200.

RCB沥青保温泵分为普通与铸钢两种材质，均带有保温夹套，保温泵适用于常温下有凝固性或结晶而通过加温并保持一定温度又容易流动且有润滑性的液体，以及高寒地区室外安装和工艺过程中需要保温的场合，泵开始工作时首先预热降低了泵的起动功率。适用于输送有腐蚀性或无腐蚀性、卫生条件要求较高的液体，输送介质不含固体颗粒，温度不高于350℃，粘度为5cSt——1500cSt的液体，如各种化工原料、灌装医药、食品、化妆品、农药、洗涤剂、印染、酿造、树脂、胶类等行业。该泵传动方式有电机直联和减速机两种，当液体粘度超过1500cSt时，应采用减速机传动。RCB asphalt heat pump can be divided into ordinary and cast steel material, with thermal insulation jacket, heat pump under applicable interesting coagulability and crystallization and by heating and maintain a certain temperature and easy flow and lubricity of liquid, in the process of the high altitude and outdoor installation process and need to heat preservation, pump starts to work when the first preheating reduced the starting power of the pump. Applicable to transport corrosive or non-corrosive, health conditions to demand higher liquid, medium not containing solid particles, the temperature is not higher than 350℃, the viscosity of liquid for 5 CST - 1500 CST, such as filling a variety of chemical raw materials, pharmaceutical, food, cosmetics, pesticide, detergent, printing and dyeing, brewing, resin, rubber and other industries. The pump drive way has two kinds of motor and deceleration machine, when more than 1500 CST liquid viscosity reducer drive should be adopted.

沥青保温泵的泵体设有空心夹层，并设有进出口法兰，可用于导热油、蒸气、热水、等媒体对输送的液体和泵进行加热保温及冷却该泵传动方式有电机直联和减速机两种，当液体粘度超过1500cSt时，应采用减速机传动。Asphalt heat pump pump body has a hollow interlayer, with import and export of flange, can be used in the thermal oil, steam, hot water, such as the media for the transportation of liquid and pump heat insulation and cooling ways there are to the pump drive motor and deceleration machine two, when more than 1500 CST liquid viscosity reducer drive should be adopted.

| | | |
|-----------|-------------------------|----------------|
| 输送聚氨酯粘接剂泵 | NYP220B高粘度泵 | 上海宝钢化工有限公司 |
| 渣油上料泵 | NYP220B-RU-T1-W12高粘度泵 | 双钱集团股份有限公司 |
| 消防泡沫灭火剂泵 | SNH660R54E6.7W1三螺杆泵 | 江苏恒力化纤有限公司 |
| 输送泡沫原液泵 | NYP220B-RU-T1-J-W12高粘度泵 | 烟台万华聚氨酯股份有限公司 |
| 原油供油泵 | SNS120R42U12.1W21三螺杆泵 | 天津新港船舶重工有限责任公司 |
| 原油污油回收泵 | SNH940R46E6.7W2三螺杆泵 | 广州黄埔造船厂 |
| 螺杆式输油泵 | SNH940R46E15YW3三螺杆泵 | 山东省威海船厂 |
| 输送油浆泵 | SNH940R42U12.1W21三螺杆泵 | 江西江洲联合造船有限责任公司 |
| 输送重质油泵 | SNH940R42E6.7W1三螺杆泵 | 中国正新橡胶公司 |
| 输送含有污水泵 | G70-1P-W102单螺杆泵 | 青岛丽东化工有限公司 |
| 输送表面活性剂泵 | G35-1V-W102单螺杆泵 | 珠海BP化工有限公司 |
| 粘合剂卸料泵 | NYP220B-LU-T1-W12高粘度泵 | 正和集团股份有限公司 |
| 双出口三螺杆泵 | 3G45 × 4C2三螺杆泵 | 陕西延安发电厂 |
| 立挂式三螺杆泵 | 3G45 × 6C2三螺杆泵 | 陕西韩城发电厂 |
| 输送热熔胶泵 | NYP-440不锈钢高粘度泵 | 宜昌兴发集团有限责任公司 |

| | | |
|-----------|-------------------------|----------------|
| 输送压敏胶泵 | NYP110-RU-T2-J-W51高粘度泵 | 中国北方化学工业（集团）有限 |
| 输送酒精胶泵 | NYP220B-LU-T1-J-W12高粘度泵 | 风神轮胎股份有限公司 |
| 输送固体胶泵 | NYP110-RU-T1-J-W11高粘度泵 | 四川龙蟒集团有限责任公司 |
| 高粘度固体胶泵 | NYP110-LU-T1-J-W11高粘度泵 | 广东华润涂料有限公司 |
| 输送脱漆脱胶剂泵 | NYP110保温高粘度泵 | 云南南磷集团股份有限公司 |
| 环保型胶类泵 | NYP220B高粘度泵 | 湖北新洋丰肥业股份有限公司 |
| 输送防水胶泵 | NYP220B-LU-T1-J-W12高粘度泵 | 山东西水橡胶集团有限公司 |
| 输送合成胶粘剂泵 | NYP220B-RU-T1-J-W12高粘度泵 | 红太阳集团有限公司 |
| 输送聚氨酯密封胶泵 | NYP320B-RU-T2-W51高粘度泵 | 浙江远东化纤集团有限公司 |
| 输送耐高温硅胶泵 | NYP220保温高粘度泵 | 四川化工控股（集团）有限责 |
| 水电专用螺杆泵 | 3G60 × 3C三螺杆泵 | 陕西渭河发电厂 |
| 水电站浸没三螺杆泵 | 3G80 × 6C三螺杆泵 | 陈村水力发电厂 |