压力机,冲床, 凹凸牌 18.5（kw）

产品名称	压力机,冲床, 凹凸牌 18.5（kw）
公司名称	上海第二锻压机床厂
价格	.00/台
规格参数	品牌:凹凸牌 型号:J21G-60 主电机功率:18.5（kw）
公司地址	中国 上海市 长宁区北翟路1041号
联系电话	86 021 62330338/62298881/62591919 13801787291

产品详情

品牌	凹凸牌	型号	J21G-60
主电机功率	18.5（kw）	公称压力	600（kn）
滑块行程	30（mm）	行程次数	500（次/min）
最大装模高度	260（mm）	喉口深度	245（mm）
工作台尺寸	720*450（mm）	滑块底面尺寸	400*320（mm）

机床介绍：1．机身采用钢板焊接整体结构，刚性好，整体造型美观。2．采用气缸平衡、动平衡装置和两组直线滚动轴承作为滑块的辅助导向，确保了本机在高速运转中的稳定性和精确性。3．采用液压过载保护装置，极大地提高了机床、模具的安全性，恢复工作简便快速。4．本机封闭高度通过制动电机调节和锁紧装置，彻底消除了冲压过程中封闭高度变化的可能性。5．本机采用自动润滑、冷却装置，确保机床正常工作，保持冲压精度。6．本机采用变频调速器，可实现主电机无级变速，极大地提高了机床的安全性，可靠性。

brief introduction：

1. all welded steel frame with high rigidity and beautiful appearance.2. pneumatic cylinder is adopted to make equipoise, dynamic equilibrator andtwain linear roll bearings are adopted for assistant guide of ram in order toensure the running of machine stable and accurate under high speed.3. the over loading protector is adopted in this press, the safety of machineand dies is maximized, and the machine continues to run easily and quickly.4. the max. shut height may be adjusted by brake motor, eliminate thepossibility of variation shut height during punching working-piece.5. automatic lubricating system and cooling device, so as to ensure that themachine runs well and punching is high accuracy.6. a frequency conversion timing device is used to achieve adjustable speedfor main motor of machine, enhance the safety and reliability of machine.