

10.4	1		10.8	2.75		11.2	4.3
10.4	2.2		10.8	2.8		11.2	7.6
10.4	2.5		10.8	3		11.3	1.2
10.4	2.8		10.82	1.28		11.3	1.3
10.4	4		10.82	1.78		11.3	1.6
10.45	2		10.85	2.75		11.3	1.75
10.46	5.33		10.9	1.25		11.3	2
10.5	1		10.9	2.03		11.3	2.2
10.5	1.5		11	0.7		11.3	2.4
10.5	1.75		11	1		11.3	2.5
10.5	1.8		11	1.2		11.3	2.7
10.5	1.83		11	1.25		11.4	1.7
10.5	1.9		11	1.3		11.4	2.1
10.5	2		11	1.5		11.4	4.4
10.5	2.25		11	1.6		11.5	1
10.5	2.3		11	1.75		11.5	1.25
10.5	2.4		11	1.8		11.5	1.3
10.5	2.5		11	1.85		11.5	1.5
10.5	2.6		11	1.9		11.5	1.6
10.5	2.7		11	2		11.5	1.78
10.5	3		11	2.2		11.5	1.9
10.5	3.25		11	2.25		11.5	2
10.5	3.5		11	2.3		11.5	2.1
10.5	4.5		11	2.4		11.5	2.2
10.5	5.9		11	2.5		11.5	2.4
10.52	1.83		11	2.75		11.5	2.5
10.57	1.5		11	2.8		11.5	2.7
10.6	1		11	3		11.5	2.8
10.6	1.3		11	3.2		11.5	3
10.6	1.8		11	3.5		11.5	3.5
10.6	2		11	4		11.5	4
10.6	2.3		11	4.5		11.6	1.2
10.6	2.4		11	5		11.6	1.6
10.6	2.6		11	5.2		11.6	1.7

10.6	2.65		11	5.3		11.6	1.78
10.6	4.5		11	5.5		11.6	2.3
10.6	6.7		11	6		11.6	2.4
10.64	1.12		11	7		11.6	2.5
10.69	3.53		11	8		11.6	2.8
10.7	1.1		11.08	1.8		11.6	2.9
10.77	2.95		11.1	1.2		11.6	2.95
10.78	2.62		11.1	1.6		11.6	6.35
10.8	1.2		11.1	2.3		11.64	1.78
10.8	1.3		11.1	5.5		11.7	2.3
10.8	1.5		11.11	1.59		11.7	2.62
10.8	1.6		11.11	1.78		11.7	2.7

d1	d2		d1	d2		d1	d2
11.7	3.5		12.1	1.6		12.6	3.5
11.7	5.8		12.1	1.7		12.6	3.6
11.77	3.15		12.1	1.8		12.64	1.78
11.8	1.5		12.1	1.9		12.65	2.77
11.8	1.8		12.1	2.1		12.7	1.6
11.8	1.9		12.1	2.2		12.7	1.7
11.8	2.1		12.1	2.35		12.7	1.8
11.8	2.3		12.1	2.4		12.7	2
11.8	2.4		12.1	2.7		12.7	2.62
11.8	2.5		12.17	1.27		12.7	2.8
11.8	2.65		12.2	1.3		12.7	3.18
11.8	2.8		12.2	1.7		12.7	3.2
11.8	3		12.2	1.9		12.7	4.96
11.8	3.53		12.2	2.5		12.72	2.62
11.8	10		12.2	2.8		12.73	1.57
11.84	2.4		12.2	3.2		12.73	1.63
11.89	1.98		12.2	4.4		12.78	6.05
11.9	1.78		12.25	2.8		12.8	1.6
11.9	2.63		12.29	3.53		12.8	1.8
11.91	2.62		12.3	1		12.8	2.4

11.99	0.81		12.3	2.4		12.8	2.8
12	1		12.3	2.5		12.8	3.2
12	1.2		12.37	2.62		12.8	4.5
12	1.5		12.37	2.76		12.9	1.24
12	1.6		12.4	1		12.9	9.9
12	1.7		12.4	1.9		12.95	0.86
12	1.75		12.4	2		13	1
12	1.8		12.4	2.18		13	1.2
12	1.85		12.4	2.6		13	1.25
12	1.9		12.4	2.7		13	1.3
12	2		12.42	1.78		13	1.4
12	2.25		12.45	1.02		13	1.5
12	2.4		12.47	1.78		13	1.6
12	2.5		12.5	1		13	1.7
12	2.7		12.5	1.1		13	2
12	2.75		12.5	1.5		13	2.15
12	2.8		12.5	1.7		13	2.35
12	3		12.5	1.75		13	2.4
12	3.05		12.5	1.8		13	2.5
12	3.2		12.5	2		13	2.6
12	3.25		12.5	2.2		13	2.7
12	3.3		12.5	2.25		13	2.75
12	3.5		12.5	2.5		13	2.8
12	3.8		12.5	2.6		13	3
12	4		12.5	2.65		13	3.2
12	4.5		12.5	2.75		13	3.28
12	5		12.5	3		13	3.5
12	5.5		12.5	3.2		13	3.6
12	6		12.5	3.5		13	3.8
12	7		12.5	4.2		13	4
12	8		12.5	8		13	4.5
12	9		12.6	2.4		13	5
12	10		12.6	2.5		13	5.5

12.07	5.33		12.6	2.7		13	6
12.1	1.3		12.6	3.25		13	8

密封咨询热线：0311-87777359 0311-87739979

qq：562404192

公司地址：石家庄市新华区北城路35号万信城市花园c9-13（万信花园底商）

本产品的加工定制是是，类型是密封圈，材质是橡胶，作用是固定密封，品牌是德氏封，型号是10.2*2.5，样品或现货是现货，是否标准件是标准件，使用温度是120（ ），使用压力是200（MPa），是否进口是是，适用范围是气缸,汽车,泵,电器,轴承，性质是耐磨损,耐腐蚀,耐高温,耐高压，内径是10.2，厚度是2.5，截面形状是O型