

无尘室用单人/双人/多人风淋室和货淋室 值得信赖

| | |
|------|---------------------------------|
| 产品名称 | 无尘室用单人/双人/多人风淋室和货淋室 值得信赖 |
| 公司名称 | 深圳市湘南高科净化设备有限公司 |
| 价格 | 11800.00/个 |
| 规格参数 | 加工定制:是 品牌:ZN 型号:ZN-2H-230 |
| 公司地址 | 深圳市龙岗区横岗街道保安社区简龙街40号3栋4楼 |
| 联系电话 | 0769-84716343 13534139400 |

产品详情

我司专业生产无尘车间专用净化设备，欢迎广大客户前来洽谈，服务热线张小姐：13825288539，谢谢！

风淋室/货淋室

air shower shower room

产品介绍：product introduction 风淋室是洁净厂房和装配式洁净小室的设备，

用于吹除进入净化厂房的人体和携带物品表面

附着的尘埃，同时风淋室也起到气闸的作用，防

止未经净化的空气进入洁净区域，是进行人体净

化和防止外空气污染洁净区的有效设备。风淋室内

的空气由风机的作用经粗效过滤器进入静压箱，

经高效空气过滤器过滤后，洁净空气从风淋室的喷

嘴高速喷出，喷嘴角度可调节，可有效吹除人体或

携带物品表面附着的尘埃，吹下的尘埃再回收进入中

效空气过滤器，室内自循环以达到人、货风淋的目的。

the shower room is clean workshop and fabricated

clean room equipment small, except for blowing into the

body and purification workshop carry-on surface adhere dust, at the same time also have the shower room of function, prevent air brake check the air into the clean without purification, is the net to prevent the air pollution and the effective clean equipment. air shower room the role of the air blower by coarse efficiency filters into plenum, the efficient air filter, air from the shower room of spray from mouth nozzle angle adjustable, and can effectively blown apart human or the surface of belongings of dust and recycled into effect of indoor air filter, since people, goods circulation in order to achieve the goal.

特点：features

系统自动感应喷淋，电子机械互锁

风淋时间0~99秒可自行调节

可对开门或直角开门

automatic reaction system, electronic and

mechanical spraying mutual zoar

the 0-99 seconds time can adjust themselves

but to open or right-angle to open the door

构成材料及技术参数

constitute the material and technical parameter

外壳：不锈钢或冷板喷塑

external frame：stainless steel or cooling-plate pensu

门、底板、喷嘴及面板：不锈钢

door, floor, nozzle and panel: stainless steel

采用粗效、高效两级过滤系统

using rough effect, efficient filter system

风机：低振动、低噪音进口或国产风机

fan: low vibration, low noise, imported or domestically fan

风速：20~28m/s

winds: 20~28 m/s

型号尺寸及其他参数standard specification

| 规格型号specifications | xn-1r-129 | xn-2r-159 | xn-4r-159 | xn-1h-200 |
|--|--------------------|--------------------|--------------------|--------------------|
| 风淋室尺寸l × w × h(mm) air shower room size | 1290 × 1000 × 2050 | 1590 × 1000 × 2050 | 1590 × 2000 × 2050 | 2000 × 2000 × 2050 |
| 风淋区尺寸l × w × h (mm) the area size | 790 × 910 × 1930 | 790 × 910 × 1930 | 790 × 910 × 1930 | 1200 × 1910 × 1930 |
| 喷嘴数量nozzle number (个) (a) | 6 | 12 | 24 | 24 |
| 风速wind (m/s) | 20~28 | | | |
| 电源power | 3n 380v 50hz | | | |
| 功率power (kw) | 0.75 | 1.5 | 4.5 | 4.5 |
| 适合人数 suitable numbers | 1~2 | 1~2 | 2~4 | 多人many |
| | | | | |

*可根据用户要求制作不同规格的风淋室

according to the requirements of users can make different specifications of the shower room

本产品的加工定制是是，品牌是XN，型号是XN-2H-230，产品别名是风淋室，空气净化技术是吸附技术，HEPA高效过滤技术,其他，功率是4.5（Kw），处理风量是3000（m3/h），净化率是99.999（%），噪音是50（dB），适用领域是风淋室是洁净厂房和装配式洁净小室的设备，用于吹除进入净化厂房的人体和携带物品表面附着的尘埃，同时风淋