



	kw	0.6	0.6	0.6	0.6	0.6	0.6	0.8
200	l/min	8.5	7.38	6.37	5.43	4.56	3.77	3.05
	m3/h	0.509	0.443	0.382	0.326	0.274	0.226	0.183
	kw	0.8	0.8	0.8	0.8	0.8	0.8	0.8
250	l/min	10.6	9.23	7.96	6.78	5.70	4.71	3.82
	m3/h	0.636	0.554	0.478	0.407	0.342	0.283	0.229
	kw	1	1	1	1	1	1	1
300	l/min	12.7	11.1	9.55	8.14	6.84	5.65	4.58
	m3/h	0.763	0.665	0.573	0.488	0.410	0.339	0.275
	kw	1	1	1	1.2	1	1.2	1.2
350	l/min	14.8	12.9	11.4	9.50	7.98	6.59	5.34
	m3/h	0.89	0.775	0.669	0.569	0.479	0.395	0.320
	kw	1.2	1.5	1.5	1.5	1.2	1.5	1.5
400	l/min	17.0	14.8	12.74	10.85	9.12	7.54	6.10
	m3/h	1.02	0.88	0.764	0.651	0.547	0.452	0.366
	kw	1.5	1.5	1.5	1.5	1.5	1.5	1.8

本产品的品牌是永鹏，型号是3DP-20，材质是铸铁，驱动方式是电动，性能是耐磨，用途是流程泵，叶轮数目是单级，泵轴位置是边立式，叶轮结构是半开式叶轮，叶轮吸入方式是单吸式，原理是轴流泵