

# 工业洗衣机洗脱机水洗机洗脱两用机干洗机

产品名称	工业洗衣机洗脱机水洗机洗脱两用机干洗机
公司名称	上海洁星洗涤机械有限公司
价格	68000.00/个
规格参数	加工定制:是 种类:洗脱两用机 洗涤容量:50-100千克 (Kg)
公司地址	上海市奉贤区奉城镇川南奉公路9198号
联系电话	021-57134428 13301665776

## 产品详情

### p系列全封闭干洗机

产品名称 :	xgq-f系列变频洗脱两用机
--------	----------------

详情

### xgq-f系列变频洗脱两用机

型号	xgq-100f	xgq-70f	xgq-50f	xgq-30f
洗涤额定容量(kg)	100	70	50	30
转笼gxl(mm)	1200 × 820	1200 × 626	1070 × 610	900 × 500
洗衣转速(rpm)	32	34	36	36
高脱脱水转速(rpm)	670	670	700	720
电机功率(kw)	7.5	7.5	5.5	4
蒸汽管通径(mm)	25	25	25	20
冷热水管通径(mm)	40	40	40	25
排水管通径(mm)	140	140	140	140
耗水量(kg/一洗二漂)	1181	924	758	473
耗汽耗比(kg/kg)	0.9	0.9	0.9	0.9
自来水压力(mpa)	0.2-0.3	0.2-0.3	0.2-0.3	0.2-0.3
蒸汽压力(mpa)	0.4-0.6	0.4-0.6	0.4-0.6	0.4-0.6
噪声(db)	> 70	> 70	> 70	> 70

外形 (长 × 宽 × 高) (mm)	1770 × 1860 × 2300	1770 × 1800 × 2300	1600 × 1500 × 1920	1400 × 1380 × 1760
整机重量(kg)	3200	2700	2500	1800
<p>洗涤室、洗涤脱水桶卧式安装、热喷锌外缸、防腐蚀；内胆采用优质不锈钢材料焊接而成。关键零部件采用进口变频器采用lg，主轴承采用美国铁姆肯。采用全悬浮减震结构与变频驱动，加速平稳，有效化解机器的振动，脱水力达到270kg，脱水后衣物含水量优于国家标准，无须地基。变频器采用lg变频器，可根据需要变频调速，操作简单，电脑全自动控制系统，中文屏幕液晶显示，洗涤过程一目了然，洗涤程序随意选择，蒸汽加热及电加热可选用，排水采用下排水，可用软管引至地沟，保持室内清洁。</p> <p>加料箱采用热水冲料解决了碱粉不易溶于冷水，结垢的弊病。脱水安全控制功能，当不平衡力过大时能自动停机，高低水位自动控制系统、全电脑程序控制，兼带手动4种水位设定可选，水温自动控制任意选择，安全门锁和控制联动装置，具有保护功能（当设备运行时能拒绝开门等误操作）。</p> <p>机体和底座采用焊接结构，机器内部、外部所有结构采用抗腐能力强的环氧树脂漆，机体外部面板采用不锈钢。</p> <p>the wash room, the wash escape the bucket horizontal type installment, to spurt outside hotly the zinc the cylinder, the gallbladder uses the high quality stainless steel material welding to become. the essential spare part uses the import or the domestic example: the frequency changer uses lg, the main bearing uses american iron to be willing. uses entire aerosol absorption frequency conversion actuation, the acceleration is steady, melts machine's vibration effectively, gao tuoshi oscillation amplitude dehydrated strength achieves 270kg, after the dehydration, the clothing water content surpasses the national standards, does not need the foundation. frequency changer uses the lg frequency changer, may according to need to establish the rotational speed willfully. the computer completely automatic control system, chinese large screen liquid crystal display that the wash process is clear, the will. the steam heating and the electric heating may select, under draining water uses drains water, the available hose directed indoor clean. added the feed box to use the hot water to flush the material to solve the alkali powder not to be easy to dissolve disease. dehydration safety control function, when the balance force is not oversized the automatic stopping and reports water level automatic control system, the entire computer programmed control, the concurrently belt manual 4 kind of water level the water temperature automatic control is optional. the security door lock and the control lindage, has the protection function moves can refuse to open the door and so on misoperations). the organism and the foundation use the welding structure exterior all structures use the anti-spoiled ability strong epoxy resin varnish, the organism exterior kneading board use the stainless steel.</p>				

本产品的加工定制是是，种类是洗脱两用机，洗涤容量是50-100千克（Kg），样式是单桶，适用范围是商业用，型号是XGQ，驱动方式是滚筒式，自动化程度是全自动，脱水容量是50，品牌是好洁牌星神牌，产品类型是全新，洗涤介质是水，电源电压是380（V），额定功率是9.8（Kw），外形尺寸（长\*宽\*高）是1600\*1500\*1800（mm），净重是2000（Kg），桶材质是不锈钢