

力士乐叠加单双向节流阀Z2FS10-5-3X/V

产品名称	力士乐叠加单双向节流阀Z2FS10-5-3X/V
公司名称	苏州欣丰达机电有限公司
价格	.00/个
规格参数	加工定制:否 类型:叠加阀 材质:铸钢
公司地址	苏州市相城区元和街道人民路4555号繁花商业中心1幢608室一楼（注册地址）
联系电话	0512-69573446 18962522903

产品详情

力士乐部分现货供应：

z2fs6a2-4x/1qv	r900581526
z2fs6a2-4x/2qv	r900439389
z2fs6b2-4x/1qv	r900438760
z2fs6b2-4x/2qv	r900440565
z2fs62-4x/1qv	r900481623
z2fs62-4x/2qv	r900481624
z2fs10-5-3x/v	r900517812
z2fs10a5-3x/s2v	r900523578
z2fs10a5-3x/sv	r900517813
2frm6b36-3x/0.2qmv	r900205577
2frm6b36-3x/0.6qmv	r900205578
2frm6b36-3x/1.5qrv	r900205507
2frm6b36-3x/3qmv	r900205516
2frm6b36-3x/3qrv	r900205517
2frm6b36-3x/6qmv	r900205518
2frm6b36-3x/6qrv	r900205519
2frm6b36-3x/100qmv	r900205508
2frm6b36-3x/100qrv	r900205509
2frm6b36-3x/16qrv	r900205511
2frm6b36-3x/25qrv	r900205513
2frm6b36-3x/32qrv	r900205515
z4s6-1x/v	r900489356
z1s10d1-3x/v	r900417595

z1s10e1-3x/v	r900417596
z1s10f1-3x/v	r900417597
z1s10p1-3x/v	r900417590
z1s10t1-3x/v	r900417591
z1s10t2-3x/v	r900334980
z2s6-1-6x/	r900347495
z2s6-2-6x/	r900347496
z2s6-3-6x/	r900347497
z2s6-a1-6x/	r900347498
z2s6-b1-6x/	r900347501
z2s10-1-3x/	r900407394
z2s10-2-3x/	r900421985
z2s10-a1-3x/	r900407424
z2s10-b1-3x/	r900407434
	0811109131
	0811109132
	0811109133
	0811109130
	0811109135
	0811109136
	0811109137
	0811109134
	0811109139
	0811109140
	0811109141
	0811109138
	0811109143
	0811109144
	0811109145
	0811109142
	0811109147
	0811109148
	0811109149
	0811109146
zdb6va2-4x/100v	r900409889
zdb6va2-4x/200v	r900409886
zdb6va2-4x/315v	r900409893
zdb6vb2-4x/200v	r900409894
zdb6vb2-4x/315v	r900409896
zdb6vp2-4x/50v	r900409847
zdb6vp2-4x/100v	r900409933
zdb6vp2-4x/200v	r900409844
zdb6vp2-4x/315v	r900409898
zdb6vc2-4x/200v	r900411312
zdb6vc2-4x/315v	r900411318
zdb6vd2-4x/100v	r900411317
zdb6vd2-4x/200v	r900411314
zdb6vd2-4x/315v	r900411357

zdb10va2-4x/50v	r900423244
zdb10va2-4x/100v	r900424537
zdb10va2-4x/315v	r900409955
zdb10vb2-4x/50v	r900425723
zdb10vb2-4x/100v	r900409951
zdb10vb2-4x/315v	r900409956
zdb10vp2-4x/50v	r900422752
zdb10vp2-4x/100v	r900409959
zdb10vp2-4x/315v	r900409958
zdb10vc2-4x/50v	r900441974
zdb10vc2-4x/100v	r900425700
zdb10vc2-4x/315v	r900411430
zdr6da2-4x/25y	r900410808
zdr6da2-4x/75y	r900410813
zdr6da2-4x/150y	r900410849
zdr6da2-4x/210y	r900410855
zdr6db2-4x/25ym	r900449839
zdr6db2-4x/75ym	r900431771
zdr6db2-4x/150ym	r900431772
zdr6db2-4x/210ym	r900463269
zdr6dp2-4x/25ym	r900483785
zdr6dp2-4x/75ym	r900483786
zdr6dp2-4x/150ym	r900483787
zdr6dp2-4x/210ym	r900483788
zdr10da2-5x/25y	r900407334
zdr10da2-5x/75y	r900439008
zdr10da2-5x/150y	r900410884
zdr10da2-5x/210y	r900406651
zdr10db2-5x/25ym	r900426202
zdr10db2-5x/75ym	r900431509
zdr10db2-5x/150ym	r900408340
zdr10db2-5x/210ym	r900443484
zdr10dp2-5x/25ym	r900410899
zdr10dp2-5x/75ym	r900410875
zdr10dp2-5x/150ym	r900410880
zdr10dp2-5x/210ym	r900410876
zdrk6vp5-1x/50ymv	r900564543
zdrk6vp5-1x/100ymv	r900564544
zdrk6vp5-1x/210ymv	r900564545
zdrk10va5-1x/50ymv	00564546
zdrk10va5-1x/100ymv	00595461
zdrk10va5-1x/210ymv	00564547
zdrk10vb5-1x/50ymv	00564548
zdrk10vb5-1x/100ymv	00564549
zdrk10vb5-1x/210ymv	00564550
zdrk10vp5-1x/50ymv	00564551
zdrk10vp5-1x/100ymv	00564552
zdrk10vp5-1x/210ymv	00564553

dz6dp2-5x/25y	r900403077
dz6dp2-5x/75y	r900481060
dz6dp2-5x/150y	r900481061
dz6dp2-5x/210y	r900481062
dz6dp2-5x/315ym	r900513984
da6vp2-4x/100-10m	r900051309
da6vp2-4x/200-10m	r900052037
da6vp2-4x/200-17m	r900052038
da6vp2-4x/315-10m	r900051311
da6va2-4x/100-17m	r900051318
da6va2-4x/200-17m	r900204554
da6va2-4x/315-17m	r900051322
da6vk1-4x/100-17m	r900051334
da6vk1-4x/315-17m	r900051336
da6vk2-4x/100-10m	r900051337
da6vk2-4x/200-10m	r900052034
da6vk2-4x/315-10m	r900051339
da6vk2-4x/200-17m	r900205113
da10-2-5x/100-10	r900597976
da10-2-5x/100-17	r900597357
da10-2-5x/200-10	r900504453
da10-2-5x/200-17	r900597015
da10-2-5x/315-10	r900596908
da10-2-5x/315-17	r900596998
da20-2-5x/100-17	r900596761
da20-2-5x/200-17	r900597135
da20-2-5x/315-17	r900590621
da30-2-5x/100-17	r900500791
da30-2-5x/200-17	r900501857
da30-2-5x/315-17	r900503396

本产品的加工定制是否，类型是叠加阀，材质是铸钢，型号是Z2FS10-5-3X/V，品牌是REXROTH/力士乐，适用范围是液压系统，产品别名是叠加单双向节流阀，适用介质是油品，适用温度是-20-80（ ），公称压力是35（MPa），公称通径是10（mm），安装形式是法兰，工作温度是高温，类型（通道位置）是直通式，连接形式是法兰，零部件及配件是配件，流动方向是双向，驱动方式是手动，形态是柱塞式，压力环境是高压，主体材料是铸铁，规格是Z2FS10-5-3X/V