

型號.	參考資料(mm)		基本荷重 (kgf)		容許靜力矩(kgf × m)			重量	
	lmax	g	動額定負荷(c)	靜額定負荷(co)	mx	my	mz	滑塊(kg)	滑軌(kg/m)
brs15b	4000	20	850	1350	10.1	6.8	6.8	0.17	1.4
brs15bs			520	680	5.1	1.8	1.8	0.1	
brs20b	4000	20	1400	2400	24	14.6	14.6	0.26	2.6
brs20bs			950	1400	7	4.9	4.9	0.17	
brs25b	4000	20	1950	3200	36.8	22.8	22.8	0.38	3.6
brs25bs			1250	1750	17.5	6.9	6.9	0.21	
brs25bl			2600	4600	52.9	45.5	45.5	0.53	
brs30b	4000	20	2850	4800	67.2	43.2	43.2	0.81	5.2
brs30bs			1750	2400	33.6	11.6	11.6	0.48	
brs30bl			3600	6400	89.6	75.4	75.4	1.06	
brs35b	4000	20	3850	6200	105.4	62	62	1.2	7.2
brs35bs			2500	3650	62.1	20.9	20.9	0.8	
brs35bl			4800	8300	141.1	109.8	109.8	1.6	
brs45b	4000	22.5	6500	10500	236.3	137.8	137.8	2.1	12.3
brs45bl			7700	13000	292.5	210.9	210.9	2.6	

本产品的品牌是ABBA，型号是BRS20B,BRH25AL，种类是滑动导轨，滑行轨迹是直线导轨，滑块个数是1000，额定动载荷是0，材质是00，额定静载荷是00，滑轨长度是4000，轴径是0