

CJ-816R热压定型机、定型机，鞋垫制作机，PE板成型机

产品名称	CJ-816R热压定型机、定型机，鞋垫制作机，PE板成型机
公司名称	晋江市超骏机械有限公司
价格	面议
规格参数	加工定制:是 适用对象:鞋面 适用材质:皮革
公司地址	福建省晋江市池店镇凤北区345#
联系电话	86-0595-85955323 0595-85955323 18965686512

产品详情

cj-816rhot forming machine (optional safety light curtains, mold installation oil)

本机适用于pu皮、牛皮、猪皮、活动鞋底、泡棉、鞋面、针织棉成型或各式皮件热压纹成型。各类eva产品、鞋底、活动鞋垫及沙滩鞋面等材料的冷压定型、可制作成鞋垫、鞋面、鞋底、箱包、眼镜盒，手袋等产品。

技术参数：

压力：16吨（其他吨位根据客户需要定做）

模板尺寸：260毫米×360毫米（可订制不同尺寸）

电压：380v 最长压合行程：150毫米（可订制不同尺寸）

电机功率:2.2千瓦 加热板功率：1.5千瓦×8块

整机重量：1.2吨 外形尺寸:2米×0.7米×2米

this machine is suitable for pu leather, cowhide, pigskin, activities soles, foam, shoe, leather goods, all kinds of knitting cotton molding or hot embossing molding. all kinds of eva products, soles, insoles and sandals surface active materials such as cold setting, can be made into insoles, uppers, soles, bags, glasses case, handbag and other products.technical parameters:pressure: 16 tons (other tonnage according to customer needs custom-made) template size: 260 mm × 360 mm (can be ordered in different sizes) voltage: 380v maximum pressure combined stroke: 150 mm (can be ordered in different sizes)motor power: 2.2 kilowatts heating plate power: 1.5 kilowatts × 8 blockweight: 1.2 tons dimensions: 2 m × 0.7米 × 2 m

配备特点：

- 1、本机乃龙门式结构设计，承受压力大，抗张力强，寿命长。
- 2、采用进口液压配件和高压力低能耗之油压动作系统及机械保压控制回路，加压时间短，成型效果好，效率高。
- 3、配有简易油温冷却管，防止油温过高，使油封和油压配件的使用寿命达到最高。
- 4、每个工作岗位的油路系统均为独立控制，均配有自动时间控制器和计数器，可单独工作。分开对应排放，故障判断简单快捷，维修方便。
- 5、采用铝合金加热板热压成型，温控采用智能型温控系统，精度高，温度可自由调整，上下模可各别控制温度，最高温可达350度，使产品达到更完美及精确之压着成型。
- 6、可根据客户提供热定型、冷定型或二冷二热机型及不同的模板尺寸。
- 7、可选配模具安装油路，上升下降位置均可自由定位，更换模具方便快捷。
- 8、也可选装安全光幕，防止操作工人压到手指。
- 9、集中电气控制箱,电气元件分布合理,每条线都做有记号，诊断维修简单快捷，不易出故障，控制系统更为可靠。

cj-816r hot forming machine

application:

this machine suitable for hot-pressing forming & embossing forming such as: pu leather, cowhide, pigskin, movable shoe pads, sponge foaming forming, knitting cotton forming or various leather-wares embossing forming.

feature:

- 1、 this machine is a electric-heating forming, the temp can be adjusted as necessary, especially. the up & lower molding can be controlled the temp separately, the max. temp can be reached 350 since, that can be achieved more accuracy & completion for pressing forming.
- 2、 this machine is designed of double column structure which can be resisted big pressure, long servicing life and high tension resistance.
- 3、 robusted for hydraulic power and can be produced multiple products simultaneously by changing molding, time & labor saving, advance efficiency and be operated independently.
- 4、 mould dimension, force and electro-heat could be customized.

本产品的加工定制是是，适用对象是鞋面，适用材质是皮革，应用领域是鞋业,服装,印染整,其他，品牌是超骏，产品类型是全新，型号是CJ-816R，电压是380（V），规格是贰岗位,四岗位,六岗位