

# 高压静电分选机

产品名称	高压静电分选机
公司名称	滑县道口北斗星静电分离设备厂
价格	35000.00/个
规格参数	加工定制:是 适用对象:导体与非导体以及半导体 应用领域:塑料与金属
公司地址	河南省安阳市滑县道口卫西开发区18号
联系电话	0372-8118690 13213287684

## 产品详情

### 高压静电分离机

适用范围：

Scope of application:

主要应用于铝塑分选方面：铝塑板、软包装、铝塑药片包装材料、哇哈哈瓶盖、铝塑电线等铝塑复合物料的铝塑分选；铜塑分选方面：电线电缆、废旧电路板及边角料、铜塑管等铜塑复合材料的分选；其它方便分选：金属矿分选、粉煤灰脱碳分选、炉渣灰金属提取、塑料与砂子分选、茶叶与茶杆分选、亚麻籽仁与壳分选、毛发与其它物料的分选。

Mainly used in aluminum plastic sorting: aluminum plastic sorting of aluminum plastic plates, flexible packaging, aluminum plastic tablet packaging materials, Wahaha caps, aluminum plastic wires and other aluminum plastic composite materials; copper plastic sorting: sorting of wires and cables, waste circuit boards and bits and pieces, copper plastic pipes and other copper plastic composite materials; other convenient sorting: metal ore sorting, fly ash decarbonization sorting, slag ash metal extraction, plastic and sand sorting, tea leaf and tea rod sorting, flaxseed fruit and shell sorting, and hair and other material sorting.

结构特点：

Structural feature:

本设备根据不同物料的导电性在密闭的高压电场中进行分选，完全采用物料的不同物理性质进行物料的

选别，分选电晕电场采用不锈钢材料加专用电晕电极，保证了分选电场的稳定。

The equipment carries out sorting according to the conductivity of different materials in the closed high-voltage electric field and selects materials in accordance with different physical properties, and the sorting corona electric field uses stainless steel materials plus the special corona electrode to ensure the stability of the sorting electric field.

高压静电分离机技术参数：

型号 Model	外观尺寸 (mm) External dimension (mm)	转鼓直径 Rotary drum dia.		转速 (r/min) Speed	功率 (kw) Power	分选电压 (v) Sorting voltage	颗粒要求 Particle requirement
SY-1000	1800*1350*3500	320		30-900	3.6	20-60000	0.01-4
SY-1500	2300*1350*3500	5.5	20-70000		1500		
SY-1800	2650*1350*3600	7.5	20-80000		1850		