Telefunken U48

产品名称	Telefunken U48
公司名称	北京麦田中旺数码科技有限公司
价格	1.00/个
规格参数	品牌:Telefunken 型号:Elektroakustik U48
公司地址	北京市朝阳区百子湾路16号百子园5号楼A单元707室
联系电话	18600607968

产品详情

QQ:148-0362713 TEL:186-006-07968 项目经理：博乐

德律风根U48双模式管麦克风立体声设置是匹配的立体声双德律风根U48电容式麦克风。它的心形和图8极性模式，使其非常适合于单和群声乐录音，以及仪器捕获。著名的M7胶囊拥有质朴的色调响应和高声压级，并加上德律风根的BV8输出变压器和VF14K真空管。该VF14K管是德律风根的第一个插件和播放设计。

在U48一直追捧的领先专业录音捕捉两个人声和乐器。随着U48音响设备，你必须运行X / Y，M / S或Blue mlein麦克风技术的能力。专为方便起见，设置带有包括双麦克风能够供电。每个组件是手选，以便尽可能接近的每个系统尽可能在两个麦克风之间的匹配。胶囊被调谐到彼此，并且变压器和管子进行测试，以便匹配的增益和频率响应。

心型和图8极性模式 从U47磁头组件可以安装在一个放大器U48 大，镀铬进气格栅头的房子新制造M7胶囊 BV8输出变压器和VF -14K真空管 一次定制的双电源供电两种权力话筒
锁定飞行的情况下，将携带两套麦克风，电缆，木箱，和双电源 换能器冷凝器压力梯度
拾音模式心形和图8 频率响应20Hz - 20kHz的 讯噪比24分贝 最大输入声压级138分贝 电源要求专用电源
输出阻抗200欧姆股票/ 50欧姆开关 输出连接器电源= XLR- 3型 尺寸9.78 x 2.24“ （ 248 x 57毫米） LXD
重量22盎司（ 624克） 德律风根U48双模式管麦克风立体声套装 2× U48管麦克风 双电源 2个连接电缆
2个木制收纳盒

Type

Condenser Pressure Gradient

Capsule

M7 - dual sided gold sputtered center terminated

Frequency Range

20Hz / 20kHz

Polar Pattern

Cardioid and Omni

Sensitivity

approx 1.2 mvolts per dyne / cm sq

Impedance

200 ohms stock / 50 ohms switchable

SPL

138 dB

Non Linear Distortion

less than or equal to 0.5% at 100 dyne / cm sq

Equivalent Noise

24 dB

Tube Type

TELEFUNKEN Elektroakustik VF14K metal tube

Power

Dedicated Power Supply

Weight

22oz (624g)

Size

9 3/4" (248mm) length x 2 1/4" (57mm) diameter

Extras

Locking Case, NG Style Power Supply, Shock Mount, Wooden Box