

quested_hm415_active 音箱

产品名称	quested_hm415_active 音箱
公司名称	北京麦田中旺数码科技有限公司
价格	1.00/1
规格参数	品牌:quested_hm415_active 型号:quested_hm415_active 1:1
公司地址	北京市朝阳区百子湾路16号百子园5号楼A单元707室
联系电话	18600607968

产品详情

QQ:1480362713 TEL:18600607968 项目经理：博乐

The HM415 Monitoring System from Quested is a four-way active speaker designed to be Soffit mounted and used as "main monitors" for large music and film control rooms. The system is comprised of four 15" bass drivers, one 8" low-mid driver, one 3" high-mid driver, and one 1.5" high frequency driver that combine to provide effortless and articulate performance with sound pressure levels of 138 dB. The monitor is supplied with a separate electronics package containing one AP1300 amplifier, three AP800 amplifiers, and the SM748 electronic crossover/loudspeaker management system.

When used in a surround configuration, a simple modification made to the low frequency amplifiers allow the L/C/R speakers to be fed the sub or .1 channel to all twelve 15" drivers eliminating the need for additional or costly sub-woofers. The HM415 ships with 5 IEC power cables.

HM415

Driver

Bass: 4 x 15" / 38 cm Low Mid: 8" / 20 cm High Mid: 3" / 7.5 cm High: 1.5" / 3.7 cm

Maximum SPL

138 dB at 1 m

Frequency Response

20 Hz to 20 kHz \pm 2 dB

Input Connections

Gold Plated Binding Post: 1 x twin pair, 1 x triple pair Accepts 0.2" / 0.4 cm banana plugs or bare wires

Amplifier (Power)

Bass: 1850 W (RMS) into 2 Ohms Low-Mid: 450 W (RMS) into 8 Ohms High-Mid: 450 W (RMS) into 8 Ohms High
450: 450 W (RMS) into 8 Ohms

Crossover Point

Low to Low-Mid: 450 Hz Linkwitz-Riley 24 dB/oct Low-Mid to High-Mid: 2 kHz Linkwitz-Riley 24 dB/oct
High-Mid to High: 6.5 kHz Linkwitz-Riley 24 dB/oct

Dimensions (W x H x D)

41.7 x 49.6 x 21.9" / 106.0 x 126.0 x 55.5 cm

Weight

507.1 lb / 230.0 kg