

# 压缩称重传感器CLJ-5KNA原装

产品名称	压缩称重传感器CLJ-5KNA原装
公司名称	深圳市诗拓浦仪器仪表有限公司
价格	11.00/个
规格参数	精度:0.05 型号:CLJ-5KNA 等级:IP65
公司地址	深圳市宝安区沙井街道步涌二路16号同富雅苑二单元180D
联系电话	0755-23002259 18033427656

## 产品详情

压缩称重传感器CLJ-5KNA原装正品

CLJ-NA压缩称重传感器

CLJ-NA负载单元的设计考虑JIS

B7728“装载校准设备来检查材料试验机”，并且是用于验证单轴压缩试验机最适合的。校准按照JIS B7728需额外费用。

防护等级：IP65

产品特点

高精度

兼容遥感

型号：

CLJ-5KNA 5kN 2mV/V

CLJ-10KNA 10kN

CLJ-20KNA 20kN

CLJ-30KNA 30kN

精度：0.05%RO

工作温度：-30 ~ +80 ° C TCLM-NB拉压力称重传感器

TCLM-NB拉伸/压缩通用称重传感器是在一个密封的封装惰性气体包封负载传感器。它提供了高精度，高输出特性和优异的稳定性，因为它使用一个剪切梁的应变传感元件。该模型广泛用于像试验机的应用程序。

防护等级：IP 65

产品特点

高精度，高输出

精度：0.05%RO

额定温度：-30 ~ +80 ° C

型号：

TCLM-10KNB 10kN 2.5mV/V

TCLM-20KNB 20kN

TCLM-50KNB 50kN

TCLM-100KNB 100kN

TCLM-200KNB 200kN

TCLY-NA张力/压缩称重传感器

TCLY-NA是张力/压缩通用称重传感器与低调的建筑和高容量。它提供了高精度，高输出特性和优异的稳定性，因为它使用一个剪切梁的应变传感元件。该模型广泛用于像单轴试验机的应用程序。

防护等级：IP40

产品特点

高精度，高输出

型号：

TCLY-300KNA 300kN 2mV/V

TCLY-500KNA 500kN

TCLY-1MNA 1MN

TCLY-1.5MNA 1.5MN

TCLY-2MNA 2MN

精度:0.2%RO

温度范围 : -10 ~ +60 ° C

压缩称重传感器CLJ-5KNA原装正品

长期供应美国Transducer Techniques称重传感器及显示仪表

美国Transducer Techniques称重传感器GSO -150 GSO -100 GSO -500

Transducer Techniques称重传感器SLB-25 SLB-50 SLB-100 SLB-250

TLL-10K Capacity: 10,000 lbs Tension Load Cell

TLL-20K Capacity: 20,000 lbs Tension Load Cell

TLL-30K Capacity: 30,000 lbs Tension Load Cell

TLL-50K Capacity: 50,000 lbs Tension Load Cell

TLL-5K-PTB Capacity: 5,000 lbs Connector Twist Lock Option

TLL-10K-PTB Capacity: 10,000 lbs Connector Twist Lock Option

TLL-20K-PTB Capacity: 20,000 lbs Connector Twist Lock Option

TLL-30K-PTB Capacity: 30,000 lbs Connector Twist Lock Option

TLL-50K-PTB Capacity: 50,000 lbs Connector Twist Lock Option

CAL-TEDS N/A Plug & Play Option with Connector

AMP-T6 N/A Mating Assembly 6 Cond

SB0-50 Capacity: 50 lbs Calibration in Compression

SB0-100 Capacity: 100 lbs Calibration in Compression

SB0-200 Capacity: 200 lbs Calibration in Compression

SB0-300 Capacity: 300 lbs Calibration in Compression

SB0-500 Capacity: 500 lbs Calibration in Compression

SB0-750 Capacity: 750 lbs Calibration in Compression

SB0-1K Capacity: 1,000 lbs Calibration in Compression

SB0-2K Capacity: 2,000 lbs Calibration in Compression

SB0-3K Capacity: 3,000 lbs Calibration in Compression

SB0-5K Capacity: 5,000 lbs Calibration in Compression

OPTION-TC N/A Tension Calibration Option

CAL-TEDS N/A Plug & Play Option with Connector

SW0-1K Capacity: 1,000 lbs Calibration in Compression

SW0-2K Capacity: 2,000 lbs Calibration in Compression

SW0-3K Capacity: 3,000 lbs Calibration in Compression

SW0-5K Capacity: 5,000 lbs Calibration in Compression

SW0-10K Capacity: 10,000 lbs Calibration in Compression

SW0-20K Capacity: 20,000 lbs Calibration in Compression

SW0-30K Capacity: 30,000 lbs Calibration in Compression

SW0-50K Capacity: 50,000 lbs Calibration in Compression

OPTION-TC N/A Tension Calibration Option 0 to 20000 lbs.

OPTION-TC-1 N/A Tension Calibration Option 21000 lbs to 50000 lbs.

CAL-TEDS N/A Plug & Play Option with Connector

HSW-1K Capacity: 1,000 lbs Calibration in Compression

HSW-2K Capacity: 2,000 lbs Calibration in Compression

HSW-3K Capacity: 3,000 lbs Calibration in Compression

HSW-5K Capacity: 5,000 lbs Calibration in Compression

HSW-10K Capacity: 10,000 lbs Calibration in Compression

HSW-20K Capacity: 20,000 lbs Calibration in Compression

HSW-30K Capacity: 30,000 lbs Calibration in Compression

HSW-50K Capacity: 50,000 lbs Calibration in Compression

OPTION-TC N/A Tension Calibration Option 0 to 20000 lbs.

OPTION-TC-1 N/A Tension Calibration Option 21000 lbs to 50000 lbs.

CAL-TEDS N/A Plug & Play Option with Connector

压缩称重传感器CLJ-5KNA原装正品