

# IC693ALG392 高密度模拟输出模块

产品名称	IC693ALG392 高密度模拟输出模块
公司名称	泉州科道电子科技有限公司
价格	面议
规格参数	品牌:GE 型号:IC693ALG392
公司地址	泉州市鲤城区江滨南路
联系电话	0595-29885920 18050815005

## 产品详情

IC693ALG392 高密度模拟输出模块

IC693ALG392 高密度模拟输出模块

IC693ALG392 高密度模拟输出模块

IC693ALG223 Analog Input, Current, 16 Single Channels

IC693ALG223CA Conformal Coated Analog Current Input module, 16 channel single ended/8 channel differential.

IC693ALG223LT Analog Input, Current, 16 Single Channels (LT)

IC693ALG223RR Analog Input, Current, 16 Single Channels

IC693ALG390 Analog Output, Voltage, 2 Channels

IC693ALG390LT Analog Output, Voltage, 2 Channels (LT)

IC693ALG390RR Analog Output, Voltage, 2 Channels

IC693ALG391 Analog Output, Current, 2 Channels

IC693ALG391CA Conformal Coat Analog Output module, two channel current.

IC693ALG391LT Analog Output, Current, 2 Channels (LT)

IC693ALG391RR Analog Output, Current, 2 Channels

IC693ALG392 High Density Analog Output (8 Channels) voltage and current.

IC693ALG392CA Conformal Coated Analog Output module, eight channels voltage/current.

IC693ALG392LT High Density Analog Output (8 Channels) (LT)

IC693ALG392RR High Density Analog Output, 8 Channels

IC693ALG442 Analog Combo Module 4IN/2OUT

IC693ALG442CA Conformal Coated Analog module, four in and two out.

IC693ALG442LT Analog Combo Module 4IN/2OUT (LT)

IC693ALG442RR Analog Combo Module, 4In/2Out

IC693APU300 High Speed Counter (HSC)

IC693APU300CA Conformal Coated High Speed Counter

IC693APU300LT High Speed Counter (HSC) (LT)

IC693APU300RR High Speed Counter (HSC)

IC693APU301 1-axis APM motion controller module

IC693APU301RR Axis Positioning Module (APM), 1 Axis, requires (1) or (2) CBL311

IC693APU302 2-axis APM motion controller module

IC693APU302RR Axis Positioning Module (APM), 2 Axis, requires (1) or (2) CBL311

IC693APU305 I/O Processor Module

IC693APU305RR Special I/O Processor

IC693BEM320 I/O Link Interface Module (Slave)

IC693BEM320RR I/O Link Interface Module

IC693BEM321 I/O Link Interface Module (Master)

IC693BEM321RR I/O Link Interface Module (Master)

IC693BEM331 Genius Bus Controller (supports I/O and Datagrams)

IC693BEM331CA Conformal Coated Genius Bus Controller

IC693BEM331LT Genius Bus Controller (supports I/O and Datagrams) (LT)

IC693BEM331RR Genius Bus Controller

IC693CBK001 Cable Kit for High Density I/O Modules (includes CBL327 and CBL328)

IC693CBK002 Cable Kit for High Density I/O Modules (includes CBL329 and CBL330)

IC693CBK003 Cable Kit for High Density I/O Modules (includes CBL331 and CBL332)

IC693CBK004 Cable Kit for High Density I/O Modules (includes CBL333 and CBL334)

IC693CBL300 Rack Expansion Cable, I/O Expansion, 1 Meter

IC693CBL301 Rack Expansion Cable, I/O Expansion, 2 Meters

IC693CBL302 I/O Base expansion 50 feet (15 meters), continuous shield with built in terminator.

IC693CBL303 Cable, Hand Held Programmer (HHP), 2 Meters

IC693CBL304 Cable, Port Expansion, Used With PCM300

IC693CBL305 Cable, Port Expansion, Used With PCM301, PCM311, and CMM311

IC693CBL311 I/O cable for DSM324 24V I/O or APM I/O to the 44A726268-001 terminal block. 3 meters

IC693CBL312 I/O rack expansion cable, 0.15 Meters, Shielded

IC693CBL313 I/O rack expansion cable, 8 Meters

IC693CBL316 Station Manager Serial Cable for Ethernet TCP/IP

IC693CBL319 I/O cable for DSM324 24V I/O or APM I/O to the 44A726268-001 terminal block. 1 meter

IC693CBL324 I/O cable for DSM302 or DSM314 or DSM324 5V I/O. 1 meter

IC693CBL325 I/O cable for DSM302 or DSM314 or DSM324 5V I/O. 3 meters

IC693CBL327 Cable, Left Side, One - 24 Pin 90 Degree Connector, 3 Meter.

IC693CBL328 Cable, Right Side, One - 24 Pin 90 Degree Connector, 3 Meter

IC693CBL329 Cable, Left Side, Two - 24 Pin 90 Degree Connectors, 1 Meter

IC693CBL330 Cable, Right Side, Two - 24 Pin 90 Degree Connectors, 1 Meter

IC693CBL331 Cable, Left Side, Two - 24 Pin 90 Degree Connectors, 2 Meter

IC693CBL332 Cable, Right Side, Two - 24 Pin 90 Degree Connectors, 2 Meter

IC693CBL333 Cable, Left Side, Two - 24 Pin 90 Degree Connectors, .5 Meter

IC693CBL334 Cable, Right Side, Two - 24 Pin 90 Degree Connectors, .5 Meter

IC693CHS391 Base, CPU, 10 Slots, Use With CPU331/CSE331 and above

IC693CHS391CA Conformal Coated CPU 10 slot base

IC693CHS391LT Base, CPU, 10 Slots, Use With CPU331/CSE331 and above (LT)

IC693CHS391NB Base, CPU, 10 Slots, Use With CPU35x, CPU36x and CPU37x. Base only. No battery included. Battery for CPUs ordered separately.

IC693CHS391RR Base, CPU, 10 Slots, Use With CPU331

IC693CHS392 Base, Expansion, 10 Slots

IC693CHS392CA Conformal Coated 10 slot expansion base.

IC693CHS392LT Base, Expansion, 10 Slots (LT)

IC693CHS392RR Base, Expansion, 10 Slots

IC693CHS393 Base, Remote Expansion, 10 Slots (700 ft.)

IC693CHS393LT Base, Remote Expansion, 10 Slots (700 ft.) (LT)

IC693CHS393RR Base, Remote Expansion, 10 Slots (700 ft)

IC693CHS397 Base, CPU, 5 Slots, Use With CPU331/CSE331 and above

IC693CHS397CA Conformal Coated 5 slot CPU base.

IC693CHS397LT Base, CPU, 5 Slots, Use With CPU331/CSE331 and above (LT)

IC693CHS397NB Base, CPU, 5 Slots, Use With CPU35x, CPU36x and CPU37x. Base only. No battery included. Battery for CPUs ordered separately.

IC693CHS397RR Base, CPU, 5 Slots, Use With CPU331

IC693CHS398 Base, Expansion, 5 Slots

IC693CHS398CA Conformal Coated 5 slot expansion base

IC693CHS398LT Base, Expansion, 5 Slots (LT)

IC693CHS398RR Base, Expansion, 5 Slots

IC693CHS399 Base, Remote Expansion, 5 Slots (700 ft.)

IC693CHS399LT Base, Remote Expansion, 5 Slots (700 ft.) (LT)

IC693CHS399RR Base, Remote Expansion, 5 Slots (700 ft)

IC693CMM301RR Genius Communications Module, GCM (256 bits)

IC693CMM302 Communication Module, Genius (1 Kbyte) GCM+ (no datagram support)

IC693CMM302CA Conformal Coating Enhanced Genius Communications module.

IC693CMM302LT Communication Module, Genius (1 Kbyte) GCM+ (no datagram support) (LT )

IC693CMM302RR Communication Module, Genius (1 Kbyte) GCM+

IC693CMM311 Communications Module, CCM, RTU, SNP, and SNPx Protocols

IC693CMM311LT Communications Module, CCM, RTU, SNP, and SNPx Protocols (LT)

IC693CMM311RR Communications Module, CCM2

IC693CMM321 Ethernet Interface TCP/IP Module. The CMM321 no longer supports the AAUI/AUI interface. If the AAUI/AUI is required, please contact GE Global Customer Care.

IC693CMM321CA Conformal Coated Ethernet Interface module. 10Mbits, supports SRTP and Modbus TCP Client/Server. The CMM321 no longer supports the AAUI/AUI interface. If the AAUI/AUI is required, please contact GE Global Customer Care.

IC693CMM321RR Ethernet Interface Module

IC693CPU311 5-Slot Base With CPU in base (6K Bytes User Program) Battery included

IC693CPU311CA Conformal Coated CPU311 5 slot base. CPU built into base.

IC693CPU311LT 5-Slot Base With CPU in base (6K Bytes User Program) (LT)

IC693CPU311RR Base 5 - slot with CPU311

IC693CPU313 5-Slot Base With Turbo CPU in base (.6 msec), 1K Registers, (12K Bytes User Program) Battery included

IC693CPU313CA Conformal Coated CPU313 5 slot base. CPU built into base.

IC693CPU313LT 5-Slot Base With Turbo CPU in base (.6 msec), 1K Registers, (12K Bytes User Program) (LT)

IC693CPU313RR 5-Slot Base With Turbo CPU (6 msec), 1K Registers

IC693CPU321RR 10-Slot Base With CPU (3K Words) & Manual

IC693CPU323 10-Slot Base With Turbo CPU in base (.6 msec) 12K bytes User Program, Battery included

IC693CPU323CA Conformal Coated CPU323 10 slot base. CPU built into base.

IC693CPU323LT 10-Slot Base With Turbo CPU in base (.6 msec) 12K bytes User Program (LT)

IC693CPU323RR 10-Slot Base With Turbo CPU (6 msec)

IC693CPU331 CPU 331 Module (16K Bytes), The battery for the CPU is now included in the CPU backplane box.

IC693CPU331LT CPU 331 Module (16K Bytes) (LT)

IC693CPU331RR CPU 331 Module, 8K Words, Manual

IC693CPU340RR CPU 340 Module, (16K Bytes user memory), 10K Reg., 3 msec/K

IC693CPU341RR CPU 341 Module, (80K Bytes user memory), 10K Reg., 3 msec/K

IC693CPU350 CPU 350 Module (32K Bytes user memory, 4K I/O, 8 Racks), no built-in Serial Ports .22msec/K,  
The battery for the CPU is now included in the CPU backplane box.

IC693CPU350CA Conformal Coated CPU350, 32Kbytes of memory

IC693CPU350LT CPU 350 Module (32K Bytes user memory, 4K I/O, 8 Racks), no built-in Serial Ports .22msec/K  
(LT)

IC693CPU350RR CPU 350 Module (32K Bytes user memory, 4K I/O, 8 Racks), no built-in Serial Ports .22msec/K

IC693CPU351RR CPU 351 Module (4K I/O, 8 Racks)

IC693CPU352RR CPU 352 Module (4K I/O, 8 Racks, Floating Point Math)

IC693CPU360 CPU 360 Module (240K Bytes configurable user memory, 4K I/O, 8 Racks), no built-in Serial Ports  
.22msec/K, The battery for the CPU is now included in the CPU backplane box.

IC693CPU360CA Series 90-30 CPU360 with Conformal Coated.

IC693CPU360LT CPU 360 Module (240K Bytes configurable user memory, 4K I/O, 8 Racks), no built-in Serial  
Ports .22msec/K (LT)

IC693CPU360RR CPU 360 Module (240K Bytes configurable user memory, 4K I/O, 8 racks), no built-in Serial  
Ports

IC693CPU363 CPU 363 Module (240K Bytes configurable user memory), The battery for the CPU is now  
included in the CPU backplane box.

IC693CPU363CA CPU363 conformal coated. CPU supports 240K of memory, 2 serial ports and up to 4,096 I/O.

IC693CPU363LT CPU 363 Module (240K Bytes configurable user memory) (LT)

IC693CPU363RR CPU363 Module (240K Bytes configurable user memory)

IC693CPU364RR CPU364 Module (240K Bytes configurable user memory), Embedded Ethernet

IC693CPU366 CPU 366 Module (240K Bytes configurable Supports Profibus DP Master (Version 1 supported).  
One Profibus port and one RS-232 service port.

IC693CPU367 CPU 367Module (240K Bytes configurable Supports Profibus DP Slave (Version 1 supported). One  
Profibus port and one RS-232 service port.

IC693CPU370 CPU370 Plus (240K Bytes configurable user memory). Supports EZ Store (IC200ACC003).  
Requires a high capacity power supply and recommend high capacity battery. Note: The CPU37x CPUs may not  
work with Horner Electric modules due to the speed of th

IC693CPU372 CPU372 Plus Web Enabled controller (120K Bytes configurable user memory), embedded Ethernet 10/100Mbps with built-in switch. Supports EZ Store (IC200ACC003). Note: The CPU37x CPUs may not work with Horner Electric modules due to the speed of the p

IC693CPU374 CPU 374 Module (240K Bytes configurable user memory) The battery for the CPU is now included in the CPU backplane box, Embedded Ethernet 10/ 100Mbps w/built-in switch. No serial ports. Note: The CPU37x CPUs may not work with Horner Electric modules

IC693CPU374CA Conformal Coated.CPU 374 Module (240K Bytes configurable user memory) The battery for the CPU is now included in the CPU backplane box, Embedded Ethernet 10/ 100Mbps w/built-in switch. No serial ports.

IC693DNM200 DeviceNet Master Module

IC693DNS201 DeviceNet Slave Module

IC693DSM302 DSM302 motion controller module

IC693DSM302RR Series 90-30 Motion Mate DSM302 Motion Controller, 2 Axes

IC693DSM314 DSM314 motion controller module

IC693DSM324 DSM324 motion controller module for Series 90-30

IC693LBR301 90-30 Documentation Library (paper manuals covering most options)

IC693LBR302 Comprehensive University Program Student Kit- Restricted Item - For sale only to approved University Program Members

IC693MAR590 Mixed I/O, 120Vac Input (8 points), Relay Output (8 points)

IC693MAR590LT Mixed I/O, 120Vac Input (8 points), Relay Output (8 points) (LT)

IC693MAR590RR Mixed I/O, 120Vac Input (8 points), Relay Output (8 points)

IC693MCD001 Beta series servo demo case

IC693MCD001RR Demo Case, Beta Series Servo