

水性金属防腐乳液

产品名称	水性金属防腐乳液
公司名称	青岛琳可工贸有限公司
价格	20.00/千克
规格参数	品牌:diransa 型号:E1560
公司地址	中国（山东）自由贸易试验区青岛片区前湾保税港区北京路45号东办公楼一楼-2605（商务秘书公司托管地址）（A）（注册地址）
联系电话	18053207568

产品详情

THYOSIL E1560

Acrylic polymer 水性丙烯酸树脂（工业防锈防腐漆）

Description描述

Acrylic polymer emulsion recommended for manufacturing primers and glossy topcoats which are designed for commercial, institutional, and industrial maintenance markets.

The high gloss capability, corrosion resistance, hardness, and chemical resistance characteristics imparted by THYOSIL E1560 in a water based finish are typical of those associated with conventional solvent-based maintenance systems.

THYOSIL
E1560

可以配制成光泽面漆和底漆，用于工业和商业的防腐防锈漆

。具有高光泽，耐腐蚀，耐化学腐蚀以及高硬度等性能。是终结传统溶剂型防护漆的水性品。

Advantages 特性与优势

- Excellent adhesion on metallic substrates. **在金属表面具有超强的附着力**
- No prior metal treatment necessary for application. **适用于未经处理的金属表面**
- Primer formulations exhibit stability with commonly used corrosion-inhibiting pigments.
可以与常用防腐蚀颜料的配方呈现出良好的稳定性
- Very good resistance to water and alcohol. **具有优良的防水和酒精性能**

Typical Properties 典型性质

These properties are typical, do not constitute specifications.

Appearance外观	White bluish liquid 白偏蓝乳液
Solids (%) 固含量	41
pH	7.5
Viscosity at 25 ° C (cP)粘度	< 500
MFFT (° C) 成膜温度	30
Tg (° C) 玻璃化温度	40

Starting formulations using THYOSIL E1560基础配方

WHITE GRINDING白色色浆的研磨制备	
Raw material原料	
Water 水	
Dowanol DPM(2)二丙二醇甲醚	

Butyl Glycol 丁基乙二醇	
THYON PH730(1) 树脂溶液	
Aqueous Ammonia (28%) 氨水	
THYOSIL Q561(1) 表面活性剂	
THYOSIL Q202(1) 消泡剂	
TiO2 R-902 (3) 钛白粉	
Water 水	
Total 总计	