

# 聚氨酯 pu AB水 8012AB

产品名称	聚氨酯 pu AB水 8012AB
公司名称	东莞市钰城树脂科技公司
价格	28.50/KG
规格参数	品牌:YC 型号:8012
公司地址	东莞横沥镇村尾村
联系电话	15622525871

## 产品详情

聚氨酯ab水 快速成型胶。8012 8013 8014 8015 8017 8612 600 700 8400 8500 自主研发，出口品质，质量保障，媲美进口，多种选择。复模材料 广泛用于工艺品，玩具，家具，模型设计，模具制造，箱包多样化，医疗器械。。。。120s固化时间 20min脱模具时间，硬度可以调节20a-90d，我司可能为客户提供专业的设计与量身订做，产品已经出口俄罗斯，日本，越南，马来西亚等地区。获得广泛的好评。

polyurethane casting resin description--polyurethane resin polyurethane-resin is a polymer materia  
I developed material room temperature curing two-component with low viscosity small odor  
soft transparent glue for its good advantages of wear resistance yellowing resistance uv resist  
ance and never harden-sit is widely used for outdoor application  
application--polyurethane resin  
1)used in aviation railways construction sports and other aspects;  
2)surface varnish for wooden and metal; 3)insulation for storage tanks pipes cold storage b  
eer fermentation tanks cold preservation barrels 4)waterproof for building insulation  
5)used for prefabricated polyurethane sheet 6)for the products making of plastic products wear-  
resistant synthetic rubber synthetic fibers hard and soft foam products  
characteristics-- polyurethane resin good radiation resistance yellow resistance and good hardne  
ss it is very suitable for outdoor products good resistant of uv and aging non change  
hardness not easy broken no shrinkage and non deformation and good adhesive and g  
ood sunshine resistance for the long time using low viscosity and good leveling  
operation instructions-- polyurethane resin  
1 operated under the conditions of ventilation environment 2 prepare the tools and mak

be sure it is clean dry, un-oiled and not in contact with any chemical solvent. 3. weigh part a and part b exactly (multi-component part a will lead to the bottom of the bubble, multi-component b may cause surface stickiness). 4. carefully stir in the same direction to avoid a large number of bubbles; you need patience and stir until completely transparent. 5. vacuum pumping. Warm tips --polyurethane resin 1. the humidity should be less than 60% if using by hand; you would better to use a dehumidifier. 2. you would better to use metal or plastic tools instead of wooden articles. 3. you should make sure your product is very dry and can not use inks containing glycerol. 4. this product (especially b glue) can't contact with skin; otherwise please wash with plenty of water and soap. 5. resin will be cured with high temperature and cured very fast. 6. far away from children to prevent eating. Package--polyurethane resin 2kg/set or 10kg/set packing, according to customer requirements. Shelf life--polyurethane resin six (6) months when stored under dry and cool place by original package under 25°C. For more information of polyurethane resin, pls feel free to contact me.