

捷霖厂家直销喷房顶篷棉过滤棉

产品名称	捷霖厂家直销喷房顶篷棉过滤棉
公司名称	捷霖过滤材料（苏州）有限公司
价格	27.00/平方
规格参数	品牌:捷霖 型号:顶棉 尺寸:2M*20M
公司地址	周市镇陆杨富强路111号
联系电话	0151-62635376 15162635376

产品详情

喷房顶篷棉过滤棉

spray booth ceiling filter media

产品特性

- 采用抗断裂的有机合成纤维构成的高性能热熔法加工而成；递增结构，利用逐渐加密多层技术，即往纯净空气方向的纤维密度逐渐增大，较高过滤效率，可根据尘埃大小，被阻挡在不同密度的层次，更有效的容纳较多的尘埃。
- 粘性处理，滤料经过充分浸胶，因粘剂完全渗透介质而使尘埃粒子无法通过，让全面过滤的空气气流均匀扩散，形成层流状态，达到最佳的喷涂效果。
- 滤网的出风面特别致密，还增加了一层方格织网加强定型,这种结构使滤料保持较高的过滤效率和容尘量，还可以延长滤料的使用寿命，在使用c-600g和c-560g时，除了可保证良好的空气质量外，由于滤料本身阻力相对较低，因此还节约系统运行成本。
 - 滤料有全粘性、表面粘性、干性处理可供客户选择。
 - 符合欧洲和美国防火分类标准dIn53438-f1，ul900 - class2；

speciality:

it is made from the anti-break organic synthesis fiber in high-powered high melt way; gradual structure, use the technology which encrypts gradually the multi-layered; the fiber density increases gradually toward pure air; high filter efficiency; may according to the dust size, prevent them in the different density level; it accommodates many dust more effectively.

coherent processing, filtering material to pass through soaks the rubber fully, fully impregnated media with adhesive treatment makes dust particles unable to pass; uniform diffusion forms laminar flow to have perfect paint spray finish;

the wind surface of the mesh is specially compact, and also put a fishing net to strengthen it ; this structure make the filtering material keep the high filtering efficiency and large dust holding capacity; even more ,it can extend the working life; when uses c-600g and c-560g, besides can assure the good air quality, because of low resistance of the material, it also saves the systems operation cost.

it is at the customers ' choice that the material have the entire coherency, the surface viscosity, dry processing

conform to european and american classifications for nonflammability.(e.g. din53438-f1,ul900-class 2 with flameout)

用途

用于涂装工厂、喷漆房、烤漆房等空气过滤。适用于汽车厂、汽车修理厂、摩托车厂、自行车厂、家电涂装作业系统。

using:

apply to the air filtration for the painting factory, the spray workshop, stoving varnish room and so on.

apply to automotive factory, the automobile repair shop, the motorcycle factory, the bicycle factory, the operating system of the household appliances painting

型号 type	c-600g	c-560g	s-560g	af-600g	fs-600g	s-600g
材质 material	polyester	polyester	polyester	polyester	polyester	polyester
平均效率（比色法） efficiency	38%	35%	35%	41%	38%	38%
平均计重效率	99%	98%	96%	98%	98%	97%

avg.arrestance						
测试风速 air velocity	0.25m/s	0.25m/s	0.25m/s	0.25m/s	0.25m/s	0.25m/s
额定风 rated air flow	900 m ³ /h	900 m ³ /h	900 m ³ /h	900 m ³ /h	900 m ³ /h	900 m ³ /h
初阻力 initial resistance	38pa	35pa	30pa	45pa	35pa	35pa
终阻力 final resistance	450pa	430pa	400pa	430pa	450pa	450pa
最大容尘量 dust holding at tested final	430 g/m ²	400 g/m ²	380 g/m ²	400 g/m ²	430 g/m ²	450 g/m ²
过滤级别 filtration class	f5	f5	f5	f5	f5	f5
耐湿 resistance humidity	100%	100%	100%	100%	100%	100%
持续耐温 temp.resistance	120	120	110	120	120	120
瞬间耐温 temp. short peaks	140	140	120	140	140	140
正常厚度	22mm	22mm	22mm	22mm	22mm	22mm

normal thickness						
标准尺寸 (m)	1.6*21	1.6*21	1.6*21	1.6*21	1.6*21	1.6*21
roll sizes standard	2.0*21	2.0*21	2.0*21	2.0*21	2.0*21	2.0*21
	1.0*21	1.0*21	1.0*21	1.0*21	1.0*21	1.0*21

注：可按客户要求订做

note:other specifications are available on request.

