



(包括油井泵)、筛网、挤塑机及其它重型设备的工业齿轮  
 船用齿轮包括主推进器、离心泵、甲板机械如绞车、锚机、吊车、旋转装置、泵、升降机和舵机  
 非齿轮应用, 包括联轴器、螺杆以及低速运转的高负荷滑动与滚动接触轴承 Mobilgear 600 XP  
 100、150、220、320、460, 和 680 经过西门子 AG 批准, 可用于 Flender 齿轮箱

Mobilgear 600 XP68100150220320460680

ISO 68	100	150	220	320	460	680	
ASTM M D 445							
mm <sup>2</sup> /s @ 68 °C	100	150	220	320	460	680	
mm <sup>2</sup> /s @ 100 °C	8.8	11.2	14.7	19.0	24.1	30.6	39.2
ASTM D2270 °C	101	97	97	97	97	96	90
ASTM D97 °C	-27	-24	-24	-24	-24	-15	-9
ASTM D92 @15.6 °C	230	230	230	240	240	240	285
ASTM D4052 kg/l	0.88	0.88	0.89	0.89	0.90	0.90	0.91
FZG 54 FVA 54 FE 8	10 / ?	10 / ?	10 / ?	10 / ?	10 / ?	10 / ?	10 / ?
DIN 51819-3, D7,5/80- 80. mg	2	2	2	2	2	2	2

??OK??65	65	65	65	65	65	65
, ASTM						
D 2782??						
4 ? EP						
???						
ASTM						
D2783,						
?????kg 200	200	250	250	250	250	250
???????k47	47	47	48	48	48	48
gf						
FZG???D						
IN 51354						
?????						
A/8.3/90 12+	12+	12+	12+	12+	12+	12+
A/16.6/9	12+	12+	12+	12+	12+	12+
0						
????? ??	??	??	??	??	??	??
ASTM						
D665???						
?????AS 1B	1B	1B	1B	1B	1B	1B
TM						
D130, 3						
?? @ 100						
oC						
???????30	30	30	30	30	30	30
ASTM D						
1401?3m						
I???????						
@ 82oC						
?????AS						
TM D892						
??/????						
ml/ml						
??1 0/0	0/0	0/0	0/0	0/0	0/0	0/0
??2 30/0	30/0	30/0	30/0	30/0	30/0	30/0