

圆盘式疏水阀 上海阀门厂

产品名称	圆盘式疏水阀 上海阀门厂
公司名称	上海市阀门股份有限公司
价格	面议
规格参数	
公司地址	上海市嘉定区阀门基地 山东省石家庄阀门基地
联系电话	021-64822232 18964992232

产品详情

圆盘式疏水阀

该阀门利用浮力原理，浮球根据冻结水量的多少，随水位于变化而作升降自动调节阀座孔的开度，连续排放凝结水。当凝结水停止进入时，浮球靠自重降到底部，回到关闭位置，排水停止。由于排水阀座孔总是在凝结水位以下，形成水封、水汽自然分离，达到无蒸汽泄漏。 according to the principle of buoyancy, floating ball fluctuates according to condensation water level, It can automatically regulate jaw opening of valve seat aperture, draining condensation water, when condensate stops flooding in, floating ball back to the bottom based on its own weight, valve closed and draining stopped. due to water closing, in which valve seat aperture below the condensate level, steam and water separated automatically, no air leakage.

主要性能参数:main specification

公称压力nominal pressure: 1.6mpa/2.5mpa/4.0mpa	壳体试验压力shell test pressure: 2.4mpa/3.8mpa/6.0mpa
最高工作温度:250 /425 maximum wording temp(tmo)	过冷度 3 condensate depression
最高允许温度:425 /475 max temp	最高背压率:85% max backing pressure rate

主要零件材料表:materials for main parts

名称 name	材料 material
阀体、阀盖 body、bonnet	wcb/wc6/304
阀座、阀芯 body、bonnet	stl
吊桶 bucketfloat	304/316
杠杆 lever	304/316
过滤网 gauze filter	304/316

用途：utility

该阀广泛用于石油、化工、电力、纺织印染、等行业的各种蒸汽加热设备、蒸汽管网、凝结水回收工程和低过热蒸汽工况。它能迅速、自动排除积水，有效地阻止蒸汽泄漏。 it is widely in sectors of petroleum,chemical,power,printing and dyeing textile for heating and steaming system,condensation water recycling and over heating steam projects.it removes condensation water and stop leakage.