

NODECOM诺控 NC620系列模块

产品名称	NODECOM诺控 NC620系列模块
公司名称	苏州诺控通信技术有限公司
价格	面议
规格参数	
公司地址	昆山开发区伟业路18号现代广场A座619室
联系电话	400-873-5515

产品详情

nodecom nc620系列模块采用业界领先的qualcomm平台，支持evdo/cdma兼容设计，最高下载速率高达3.1mbps。nc620为用户提供标准的minipcie硬件接口，内置tcp/ip和udp/ip协议栈，集成了usb2.0、uart、pcm/analog audio、休眠唤醒等多种接口和功能，灵活性强。

nc620系列模块采用工业级设计，性能稳定，可靠性强，可适应恶劣的工作环境，广泛应用于车联网、安防监控、视频传输、工业路由、智能电网、移动支付等市场领域。

general features:

is-856-a (cdma 1xev-do revision a)

is-856 (cdma 1xev-do rev 0)

is-2000 (cdma 1xrtt)

is-95 a/b

is-707-a data

is-637-a sms

is-683-a service provisioning

is-683-b (partial)

rx diversity in 800mhz band

control via at commands(hayes 3gpp ts 27.007 and 27.005)

supply voltage range: 3.3v-4.2v

low power consumption

sleep mode <5ma

idle mode: <40ma

dimensions: 51.0 × 30.0 × 3.2mm

temperature range

normal operation: -20 ° c to 65 ° c

restricted operation: -30 ° c to 75 ° c

storage: -40 ° c to +85 ° c

interfaces:

rf connector

pci express® mini card interface

power supply

usb 2.0 full speed

uim/ruim card interface

airplane mode

uart

analog audio

pcm

reset

network status

sleep control

gpios

specifications for sms:

point-to-point mo and mt

sms cell broadcast

text and pdu mode

approvals:

srrc

cta

ccc

rohs