

# 山东云峰700L双向除渣器 内衬陶瓷

产品名称	山东云峰700L双向除渣器 内衬陶瓷
公司名称	淄博云峰工业陶瓷有限公司
价格	230.00/件
规格参数	品牌:云峰 型号:700 规格:定制
公司地址	山东淄博淄川城西刘瓦工业园
联系电话	0533-5556936 13806435563

## 产品详情

ylc-700型双向除渣器利用离心原理去除浆料中的各种轻、重杂质。除渣器上、下锥体采用pa66材质，具有较高的强度和耐磨性以及良好的弹性，上、下外壳为玻璃纤维加强的聚丙烯pp。

该除渣器具有全新的进浆设计，通过形成的加速流和较长的停留时间结合在一起，这种设计特点赋予了除渣器很高的分离作用。使用时，良浆围绕着中部空气芯进入一个长的轻杂质除渣区，未被扰动的浆流中的轻杂质紧贴空气芯而被有效从顶部分离出外。良浆则沿器壁以切线方向推出器外，配合我公司生产的150型轻质除渣器使用效果更为显著。它可用在纸浆净化系统中，除去浆料中的混合废弃物、石蜡、粘着物、塑料片、泡沫、气体、沙石、铁屑等轻、重杂质。

主要技术参数进浆能力： 500-700l/min进浆压力： 0.2-0.35mpa进浆浓度：  
0.3-1.2%单段重杂质体积排渣率： 6-8%(相对进浆流量)单段轻杂质体积排渣率：  
10-12%(相对进浆流量)

products overview:ylc - 700 type two-way slag separator using the theory of centrifugal to get rid of various light and heavy impurity in the pulp.slag on, under the cone use pa66 material, with high strength and abrasion resistance and good elastic, upper and lower case for glass fiber reinforced polypropylene pp.the slag appliances have new into the slurry design, through the form of accelerated flow and long time together, the design characteristics of slag separator high separation effect.when using, accepts around central air core into a long light impurity slag zone, disturbance of light impurities in pulp flow is not close to be effectively separated out from the top to air core.accepts the ejector along the wall to the tangent direction, cooperate with our company produces the type 150 light slag separator using effect is more significant.it can be used in the paper pulp cleaning system, remove the mixed waste pulp, paraffin wax, adhesive, plastic, foam, gas, sand, iron and other light and heavy impurities.the main technical parametersinto the slurry capacity: 500-700 l/mininto the slurry pressure: 0.2-0.2 mpainto the slurry concentration: 0.3 to 1.2%single piece of heavy impurities discharge volume rate: 6-8% (relative into the slurry flow)single period of light impurity discharge volume rate: 1-12% (relative into the slurry flow)