

山东云峰高浓双锥除渣器 厂家定制

产品名称	山东云峰高浓双锥除渣器 厂家定制
公司名称	淄博云峰工业陶瓷有限公司
价格	230.00/件
规格参数	品牌:云峰 型号:yf 规格:定制
公司地址	山东淄博淄川城西刘瓦工业园
联系电话	0533-5556936 13806435563

产品详情

双锥体高浓除渣器是纸浆净化先进设备，尤其是净化废纸纸浆效果更佳，是废纸再生利用不可缺少的关键设备之一。它利用纤维与杂质比重不同，利用离心原理使重杂质从纸浆中分离出来，达到净化纸浆的目的。该设备使用面广，既可用于高浓度纸浆的粗选净化，也可用于纸机前，对低浓度纸浆进行精选净化。

该除渣器结构简单，占地面积小，生产能力大，自动化可调试排渣操作简单，不易堵塞排渣口，净化效率高，浆料仅一次性通过除渣器，不再需要尾浆处理设备，纤维流失小。锥体耐磨，使用寿命长：没有传动，无需较多维护，有全自动和手动两种形式。

技术参数

型号功能		ftg1	ftg2	ftg3	ftg4	ftg5	ftg6	ftg7	ftg8	ftg9	ftg10
粗选4 %	压差m pa	0.02-0.0 8	0.03-0.0 9	0.03-0.1 2	0.04-0.1 3						
	流量m 3/min	0.25-0.5 5	0.5-0.95	0.75-1.6 0	1.0-3.0	2.0-3.5	3.5-5.0	5.0-6.0	6.0-7.5	7.5-10	10-11.5
	能力t/d	15-30	29-55	43-100	57-130	100-180	140-220	180-250	220-320	300-450	400-550

product description:a double cone high density cleaner pulp is advanced purification equipment, especially in the purification of waste paper pulp better, it is one of the key equipment of waste paper recycling indispensable. it uses different fibers and the proportion of impurities, so that the principle of centrifugal separation of heavy impurities from the pulp out to purify the pulp purposes. the device using a wide, both for the high consistency pulp roughing purification. before the machine can also be used for low consistency pulp cull purification.the cleaner is simple, small footprint, large capacity, automation can debug simple slagging operation. clogging tap outlet, clean and efficient, one-time only through cleaner slurry, slurry handling equipment is no longer required tail, small fiber loss. cone wear and long life: no drive, no more maintenance, there are two types of automatic and manual.

technical parameters

model function		ftg1	ftg2	ftg3	ftg4	ftg5	ftg6	ftg7	ftg8	ftg9	ftg10
roughing 4%	pressure mpa	0.02-0.08	0.03-0.09	0.03-0.12	0.04-0.13						
	flow m3/min	0.25-0.55	0.5-0.95	0.75-1.60	1.0-3.0	2.0-3.5	3.5-5.0	5.0-6.0	6.0-7.5	7.5-10	10-11.5
	processing capacity t/d	15-30	29-55	43-100	57-130	100-180	140-220	180-250	220-320	300-450	400-550