# 台湾AXE钜斧热电偶MM2-F52-20NB

| | |
|---|---|
| 产品名称 | 台湾AXE钜斧热电偶MM2-F52-20NB |
| 公司名称 | 苏州钜工电子科技有限公司 |
| 价格 | 100.00/台 |
| 规格参数 | 品牌:AXE钜斧<br>型号:MM2-F52-20NB |
| 公司地址 | 苏州工业园区万盛街28号星海国际大厦924室 |
| 联系电话 | 0512-66059945 18550457165 |

# 产品详情

台湾AXE钜斧热电偶MM2-F52-20NB

AXE电表-31/2位数可程序盘面型数字电表(显示屏0.56"/0.8")M1

( 31/2 DIGITAL PANEL METEROFPROGRAMMABLE )(DISPLAY 0.56"/0.8")

● Aux.power supper : AC110V & 220V±20%(50/6Hz)

( 辅助电源 )

● Measuring accuracy : 0.1% F.S. ±1 digit

( 精 确 度 ) (23 ±5°C) 0.2% F.S. ±1 digit(AC(RMS))

● Sampling time : 2 cycles/sec.

( 取样时间 )

● Readout range : 0~ ±1999 digit adjustable

( 显示值范围 )

● Zero (offset) range : 0- ±100 digit adjustable

( 归零调整范围 )

● Over input indication : " 1 " or " -1 "

( 过载显示 )

● Display : Red high efficiency LEDs high 14.22mm(.56")

( 显示屏 ) M1-□□□-A

Red high efficiency LEDs high 20.32mm(.8")

M1-□□□-B

● Polarity display : When input is negative " _ " display

( 极性显示 )

● Temp. coefficient : 50ppm/°C (0-50°C)

( 温度系数 )

● Dielectric strength : 2KVac/1 min. (input/power)

( 绝缘耐压能力 )

● Operating condition : 0-50°C(20 to 90% RH non-condensed)

( 使用环境条件 )

● Storage condition : 0-70°C(20 to 90% RH non-condensed