

螺杆空压机无油机水润滑机整机，维修与保养

产品名称	螺杆空压机无油机水润滑机整机，维修与保养
公司名称	合肥光徽压缩机械有限公司
价格	100.00/台
规格参数	品牌:德隆 型号:DL
公司地址	合肥市包河区马鞍山南路429号创智广场4幢1406室
联系电话	18326600632

产品详情

提供各品牌的空压机的销售与售后服务。蚌埠空气过滤器，蚌埠空压机油过滤器，蚌埠空压机油气分离器芯，蚌埠空压机转子油，及蚌埠空压机各类配件，并提供上门服务，蚌埠空压机保养；提供各品牌储气罐，各类冷干机及

其配件，上门维修服务；提供各种规格的管道过滤器和管道过滤器芯；支持定做非标件。24小时免费电话咨询：周主任 +86 18326600632 ，邮箱 3416890856@qq.com ，QQ：3416890856 ，MSN: zhougp0001@outlook.com。

德隆智能式双螺压缩机

真正的原装主机系统

螺杆主机是螺杆空压机的核心部件，直接决定能效与噪音。

GuangHui压缩机均采用德国制造原装主机，现金的SAP转子型线，锻钢材质与德国转子热处理加工技术，比国内球磨铸铁与研磨的转子材质加工技术领先一个档次，效率差将近15%。

标准主机配置，低速传动

GuangHui每台空压机均选用标准或更高一档的压缩主机生产，坚决杜绝小马拉大车高转速现象出现。

主机选配时，严格以低转速与主机最佳比功率为原则，真正的低转速与低比功率，真正达到节能与静音的最佳效果。

独特的冷却流畅设计

先进的导向设计，是冷却交换更完全。

内部金属管材质的气、油路设计，使润燥冷却油路运行更高速，最及时的带走主机热量，真正避免了主机高温现象的出现。

功能特点：排气温度（ ）：风冷<环境温度+15 ，电源：380V 50HZ ，适用环境温度：-5 ~45 ，驱动方式：直连/皮带；启动方式：星三角启动；冷却方式：风冷。

另外本公司提供蚌埠空压机无油水润滑机，蚌埠空压机涡旋机，蚌埠空压机低压机，蚌埠空压机两级压缩空压机等，欢迎来电洽谈：周主任 +86 18326600632 ，邮箱 3416890856@qq.com ，QQ：3416890856 ，MSN: zhougp0001@outlook.com 。

Provide various brands of air compressor air filters, oil filters, oil and gas separator batteries, oil compressor rotor, compressor and various accessories, and provide on-site services; providing brand gas tank, all kinds of cold and dryer

Its accessories, home maintenance services; provide a variety of pipes and pipe filters filter core; support customized non-standard parts. 24-hour free telephone consultation: Zhou +86 18326600632, email 3416890856@qq.com, QQ: 3416890856, MSN: zhougp0001@outlook.com.

Deron smart twin screw compressor

The real original host system

Screw screw air compressor is the heart of the host member, directly determine the energy efficiency and noise.

GuangHui compressors are used in manufacturing original host Germany, SAP's cash rotor profile, forged steel rotor material and heat treatment processing technology in Germany, than the domestic milling and grinding of cast iron rotor materials processing technology leader in a grade, low efficiency of nearly 15%.

Standard host configuration, low speed

GuangHui each compressor are made of standard or compression host a higher production profile, and resolutely put an end to small high-speed horse-drawn carts phenomenon.

Host matching, strictly on low speed with the host optimum ratio of power principle, truly low-speed and low-power ratio, thereby achieving the best results and energy saving mute.

Unique cooling fluid design

Advanced design guide, the exchange is more complete cooling.

Inside the metal tube material gas, oil design, the cooling passage Yun Hwan run faster, hosts the most timely away the heat, to avoid the emergence of a true master of the high temperatures.

Features: exhaust gas temperature (): Air Cooled <ambient temperature of + 15 ， power supply: 380V 50HZ,

Ambient temperature: -5 ~ 45 , drive: Direct Connect / belt; Start: star delta starter; cooling: air-cooled.

In addition the company provides no oil lubrication machines, scroll machine, low pressure, two-stage compression compressor, etc., please call to discuss: Zhou +86 18326600632, email 3416890856@qq.com, QQ: 3416890856, MSN: zhougp0001 @ outlook .com.