

奥地利 Qness 硬度计 - 竞现科技

产品名称	奥地利 Qness 硬度计 - 竞现科技
公司名称	深圳竞现科技有限公司
价格	面议
规格参数	品牌:奥地利Qness 型号:Q250/Q750 C 等级:一级
公司地址	深圳市南山区南园枫叶公寓B座416
联系电话	0755-2843-3163 188-9883-8325

产品详情

硬度测试应用

hardness testing redefined.

brinell

din en iso 6506, astm e-10

hbw 1/1 /2.5 /5 /10 /30

hbw 2.5/6.25 /15.6 /31.25 /62.5 /187.5

hbw 5/25 /62.5 /125 /250 /750

hbw 10/100 /250 /500

hbt (not acc. to standards)

vickers

din en iso 6507, astm e-384

hv0.5 hv1 hv2 hv3 hv5 hv10

hv20 hv30 hv50 hv100

hvt (not acc. to standards)

令人信服的优点

convincing benefits

全自动测试进程：

采用电子加载及试验力闭环控制的方式

fully automated test process with electronic weight application and closed-loop control

操作简单：

自动图像评估和亮度调整、快速自动对焦、人工重新测量、

多种统计功能等。

simple operation: automatic image evaluation and brightness regulation, fast auto-focus,

manual re-measurement, numerous statistical functions inter alia.

电容式12"触摸屏显示器：

可以精确显示压痕图像，且带有usb接口

capacitive 12" touch display: for precise display of hardness testing points

with built-in usb port

载物台高度调节：

通过预应力滚轴丝杠

height-adjustable test table: via snug-fit roller-bearing spindle guide

载物台的支撑：

测试时不会产生任何高度上的位移

swivel suppressor: no lengthy re-tooling breaks for inaccessible test points.

6位转塔台：

伺服器电机和伺服控制系统

6-position tool changer: servo-drive and servo-positioning

试验力范围	0.5 - 250 kg	
test load area	(4.9 - 2450 n)	

显示器/软件	电容式12"触摸屏显示器	
display / software	capacitive 12" touch display	
载物台	∅ 100 mm (option ∅ 220 mm)	
test table		
可测试工件的最大重量	没有限制	
max. work piece weight	unlimited	
仪器净重	125 kg 150 kg	
weight of basic device		
数据接口	1 x usb (front) 2 x usb, 1 x rs232, 1 x rj45 (ethernet)	
interfaces		
电源	230~1/n/pe, 110~1/n/pe	
power supply		
最大输入功率	~ 360 w	
max. power input		