

# 122转星108.2专用头Ku双本振高频头

产品名称	122转星108.2专用头Ku双本振高频头
公司名称	安徽站乾科技有限公司
价格	30.00/只
规格参数	品牌:starcom 本振:9750-10600 输出:单输出
公司地址	安徽省合肥市庐阳区洪河路18号
联系电话	0551-5657425 15240026815

## 产品详情

122DISH转星108.2专用头 ( Ku双本振9750/10600MHz )

此款高频头，也有双输出，四输出供应

如有需要，请加Q:2507083042 微信：Lizyzhou919 手机：15240026815

我们支持淘宝交易，请加QQ或者微信，索要链接。我们将竭诚为您服务！！

Ku双本振单输出高频头，款式众多，都是出口的高质量高频头

参数如下：

Input Frequency	Low Band:10.70 GHz -11.70GHz
-----------------	------------------------------

High Band:11.70 GHz -12.75GH

Output Frequency

.Low Band:950-1950MHz

High Band:1100-2150MHz

L.O. Frequency

9.75/10.6GHz

L.O. Stability

Low Band:  $\pm 1$  MHz(-40centigrade to +70centigrade)

High Band:  $\pm 1$  MHz(-40centigrade to +70centigrade)

Noise Figure

0.2 dB

Conversion Gain

60dB

Gain Flatness

+/-2dB

Input VSWR	2.5:1(max)
Output VSWR	2.0:1(max)
Output Connector	F-female Connector
Output Impedance	75
Cross Polar Isolation	20dB(min)
Supply Voltage	1)Ca:11.5-14.0v(Vertical Polarization) 13VDCType 2)Cb:16.0-19.0v(Horizontal Polarization)18VDCType
Direct Current	150mA
Control Signals	1).Low Band:Ca or Cb(see below) 2).High Band:Cc or Cb(see below)  3)Cc:continues 22KHz
Operating Temperature	-40centigrade to +70centigrade

Storage Temperature	-40centigrade to +80centigrade
Relative Humidity	0%-95%
Phase Noise	1)-50dBc/Hz@1kHz(max) 2) -75dBc/Hz@10kHz(max) 3) -95dBc/Hz@100kHz(max)
Image Rejection	45 dB (min)