

不锈钢置物架轮管机 竹节管成型机

产品名称	不锈钢置物架轮管机 竹节管成型机
公司名称	佛山市杭滔机械设备有限公司
价格	500.00/件
规格参数	品牌:杭滔 型号:LG
公司地址	佛山市顺德区北滘镇西海二支工业区南路25号
联系电话	18620518716

产品详情

PGM系列滚动式全自动液压轮管机

PGM Series Automatic Rolling Type Hydraulic Pipe Grooving Machine

整机性能特点

轮管机也叫竹节管机，滚槽机，主要用于金属竹节管加工，广泛应用于生产置物网架、货架、衣柜架等的立柱圆管、五金家电、照明灯饰、家居装饰、工艺品等领域。

该设备采用液压油缸定位，电机驱动旋转，机械齿轮传动和PLC微电脑控制，结构紧凑、运行平稳、维修方便、加工精度高，操作简单，只要将圆管放入两轧辊间即可，是管类美化加工的理想设备。

也可根据客户需要，根据金属管尺寸，各种规格竹节管的节距和凹槽形状，特殊定制机器和轧轮模具及滚刀。

Features of the Machine

Roll Groover,also called Steel Tube Bamboo Joint Forming Machine,

Channeling Machine,is mainly used for processing bamboo joint and groove on metal tube, widely applied in the production of the rack, shelf, wardrobe frame, hardware appliances, lighting, decoration, handicrafts,Home Furnishing,and so on.

The equipment adopts hydraulic cylinder positioning, motor driven rotation, machinery gear drive and PLC microcomputer control, structure compact,

operation stable, convenient maintenance, high precision, simple operation: only need to load the round tube into the two rolls, then OK. It is an ideal equipment for tube beautification processing.

According to customer needs, different size of metal tube, different bamboo joint pitch and groove shape, also can produce the machine specially with different rolling mould and channeling cutter.

主要技术参数

Main Technical Parameters

额定电压Rated Voltage	380V or Customized AC 3PH 50/60Hz
额定功率Rated Power	4.4KW
工作气压Input Air Pressure	More than 0.2Mpa
管子加工长度Pipe Length	750mm, 1000mm, 1500mm
加工速度Producing Speed	20-30Pipes /Min
外形尺寸Overall Dimensions	130cm*100cm*190cm
设备重量Machine Weight	750Kg