Vgate iCar2 WIFI OBDII

	Vgate iCar2 WIFI OBDII
	120.00/PCS
	:cheery :CTC065-01
	0755-21630520 18926583027

Vgate iCar2 WIFI OBDII scan tool ELM327 WIFI OBD2 Scanner iCar 2 WIFI vgate OBD diagnostic interface for IOS iPhone iPad Android 8 colors

Vgate icar2 WIFI is a small adapter that plugged into the vehicle OBD-connector. On WIFI, it connects to any computer, tablet or smartphone, With associated diagnostic procedures.

Features:

* Small size, compact structure. Plug and never unplug

* Stable wireless connection

* No wires or batteries (adapter is powered by the diagnosis size sockets)

* Stop communication, wait half an hour, auto sleep

* Supports all OBDII protocols

* The adapter uses the fastest and most reliable ARM chips

Doing these simple operations, you will be able:

* Read, erase and display code descriptions problems - both standard and

spetskodov manufacturers.

* Measure the fuel consumption.

* Display real-time operating performance of the car, such as momentum,

vehicle speed, oil pressure, coolant temperature, engine load, intake manifold

pressure, throttle position, the values of oxygen sensors, air intake

temperature, and more.

* Turn off the MIL (signal Check Engine).

* Download data to external media in a variety of formats for later printing.

* Record various parameters, display graphics in real time, and more.

With iCar you will be able to perform a complete computer diagnostics car and even to correct minor faults without resorting to service stations.

iCar 2 scantool is a high-quality automotive scanning tool, supports all OBD-II

Protocols:

0.Automatic

1.SAE J1850 PWM (41.6 Kbaud)

2.SAE J1850 VPW (10.4 Kbaud)

3.ISO 9141-2 (5 baud init, 10.4 Kbaud)

4.ISO 14230-4 KWP (5 baud init, 10.4 Kbaud)

5.ISO 14230-4 KWP (fast init, 10.4 Kbaud)

6. ISO 15765-4 CAN (11 bit ID, 500 K baud)

7. ISO 15765-4 CAN (29 bit ID, 500 K baud)

8. ISO 15765-4 CAN (11 bit ID, 250 K baud)

9. ISO 15765-4 CAN (29 bit ID, 250 K baud)

A. SAE J1939 CAN (29 bit ID, 250*K baud)

B. USER 1 CAN (11*bit ID, 125*K baud)

C. USER 2 CAN (11*bit ID, 50*k baud)

*default settings (user adjustable)

The type of support:

1. Works with all OBD-II compliant vehicles

2. Wireless (wifi version) 10-20 meter

3. iCar (wifi version) support for software
applications for ios (iphone4 / 4s /5 /5s /ipad /mini), Android, java, etc)

Package List:

1x iCar 2

1x CD

1x Carrying box

Remark:

We provide Multi-color for choice (8 kinds). Please kindly leave a message to us which color you want. Otherwise, we will ship it in random. Thanks!