

## Vgate iCar3 Wifi Elm327

产品名称	Vgate iCar3 Wifi Elm327
公司名称	深圳市车维科技有限公司
价格	120.00/PCS
规格参数	品牌:cheery 型号:CTC065-03
公司地址	深圳市宝安区
联系电话	0755-21630520 18926583027

## 产品详情

Vgate iCar3 Wifi Elm327 Wifi iCar III Code Reader Support All OBDII Protocols Cars iCar 3 Scan Tool for Android/IOS/PC

Vgate iCar III is a small adapter that plugged into the vehicle OBD-connector.

On WIFI, it connects to any computer, tablet or smartphone, With associated diagnostic procedures.

Attention:

We provide Multi-color for choice (5 kinds). Please kindly leave a message to us which color you want. Otherwise, we will ship it in random. Thanks!

Features:

\* Supply voltage(VDD):12V

- \* Work temperature range: -20 ~ +70 degree
- \* Storage temperature range: -40 ~ +125degree
- \* RF sensitivity(Basic Rate): -85db
- \* Modulation Mode: GFSK
- \* Frequency Range:2402 ~ 2480MHZ
- \* Transmission Range:10M
- \* Bluetooth Profile:SPP
- \* UART Params:38400,8,n,1
- \* Small size, compact structure.
- \* Stable wireless connection
- \* No wires or batteries (adapter is powered by the diagnosis size sockets)
- \* Stop communication, wait half an hour, auto sleep
- \* Supports OBDII protocols
- \* The adapter uses the fastest and most reliable ARM chips

#### Function:

- \* Read, erase and display code descriptions problems - both standard and spetskodov manufacturers.
- \* Measure the fuel consumption.
- \* Display real-time operating performance of the car, such as momentum, vehicle speed, oil pressure, coolant temperature, engine load, intake manifold pressure, throttle position, the values of oxygen sensors, air intake temperature, and more.
- \* Turn off the MIL (signal Check Engine).
- \* Download data to external media in a variety of formats for later printing.
- \* Record various parameters, display graphics in real time, and more.

With iCar3 you will be able to perform a complete computer diagnostics car and even to correct minor faults without resorting to service stations.

iCar 3 scantool is a high-quality automotive scanning tool, supports all OBD-II

Protocols :

0. Automatic

1. SAE J1850 PWM (41.6Kbaud)

2. SAE J1850 VPW (10.4Kbaud)

3. ISO9141-2 (5 baud init, 10.4Kbaud)

4. ISO14230-4 KWP (5 baud init, 10.4 Kbaud)

5. ISO14230-4 KWP (fast init, 10.4 Kbaud)

6. ISO15765-4 CAN (11bit ID, 500 Kbaud)

7. ISO15765-4 CAN (29bit ID, 500 Kbaud)

8. ISO15765-4 CAN (11bit ID, 250 Kbaud)

9. ISO15765-4 CAN (29bit ID, 250 Kbaud)

A. SAE J1939 CAN (29bit ID, 250\*Kbaud)

B. USER1 CAN (11\*bit ID, 125\*Kbaud)

C. USER2 CAN (11\*bit ID, 50\*kbaud)

\*default settings (user adjustable)