

一洋五金专业生产低烟无卤型金属软管

产品名称	一洋五金专业生产低烟无卤型金属软管
公司名称	成都一洋五金有限公司
价格	4.61/米
规格参数	品牌:一洋五金Drflex 型号:LFH-10S 19S 规格: 6- 75
公司地址	成都市高新西区天目路77号
联系电话	13348931787

产品详情

低烟毒镀锌金属软管 Low Fire Hazard Galvanized Steel Flexible Conduit 材 质：镀锌钢带

PVC 包塑：黑 防护等级：IP65 耐温范围：-10 - +90

拉 力：1700N Materials: Galvanized Steel PVC Coated: Black

Protection Rating: IP65 Temperature Range: -10 - +90 Tension : 1700N

型号 Part No. 规格 通径 内径(mm) 外径(mm) 弯曲半径 (mm) 包装 (m/coil) 镀锌钢带 (S) Inch mm I.D.

O.D. Bending Radius Packing LFH-10S 3/8" 12 12.30-12.60 16.50-16.80 60.0 50 LFH-11S 1/2" 16 15.70-16.00

20.50-20.80 85.0 50 LFH-12S 3/4" 20 19.70-20.00 25.30-25.60 100.0 50 LFH-13S 1" 25 25.30-25.80 30.70-31.20

120.0 50 LFH-14S 1-1/4" 32 32.30-32.80 38.50-39.00 150.0 25 LFH-15S 1-1/2" 38 38.30-38.80 45.70-46.20 180.0

25 LFH-16S 2" 51 50.00-50.50 58.80-59.30 220.0 20 LFH-17S 2-1/2" 64 62.50-63.20 73.50-74.00 310.0 10

LFH-18S 3" 75 73.00-73.70 84.50-85.20 350.0 10 LFH-19S 4" 100 97.50-98.50 109.50-110.50 410.0 10

镀锌铁皮制成，表面低烟毒PVC被覆， Galvanized Steel Core, PVC coated.

轻质结构，绝佳弯曲性能及低烟毒耐燃特性， Light weight style, excellent flexibility and

使用于任何狭小空间或通风不良， low fire hazard low smoke. 注重生命安全等配管区域。 Use

for the place with poor ventilation or the environment needs more secure care of any narrow

space for electrical wiring applications.

低烟毒不锈钢金属软管 Low

Fire Hazard Stainless Steel Flexible Conduit 材 质：不锈钢钢带 PVC 包塑：黑

防护等级：IP65 耐温范围：-10 - +90 拉 力：1700N

Materials: Stainless Steel PVC Coated: Black Protection Rating: IP65

Temperature Range: -10 - +90 Tension : 1700N 型号 Part No.

规格 通径 内径(mm) 外径(mm) 弯曲半径 (mm) 包装 (m/coil) 不锈钢钢带 (SS) Inch mm I.D. O.D. Bending

Radius Packing LFH-10SS 3/8" 12 12.30-12.60 16.50-16.80 60.0 50 LFH-11SS 1/2" 16 15.70-16.00 20.50-20.80

85.0 50 LFH-12SS 3/4" 20 19.70-20.00 25.30-25.60 100.0 50 LFH-13SS 1" 25 25.30-25.80 30.70-31.20 120.0 50

LFH-14SS 1-1/4" 32 32.30-32.80 38.50-39.00 150.0 25 LFH-15SS 1-1/2" 38 38.30-38.80 45.70-46.20 180.0 25

LFH-16SS 2" 51 50.00-50.50 58.80-59.30 220.0 20 LFH-17SS 2-1/2" 64 62.50-63.20 73.50-74.00 310.0 10

LFH-18SS 3" 75 73.00-73.70 84.50-85.20 350.0 10 LFH-19SS 4" 100 97.50-98.50 109.50-110.50 410.0 10

不锈钢制成，表面低烟毒PVC被覆， Stainless Steel Core, PVC coated.

轻质结构，绝佳弯曲性能及低烟毒耐燃特性， Light weight style, excellent flexibility and

使用于任何狭小空间或通风不良， low fire hazard low smoke. 注重生命安全等配管区域。 Use
for the place with poor ventilation or the environment needs more secure care of any narrow
space for electrical wiring applications.