

胀紧联结套 . (N.m)

| | |
|------|--------------------------------------|
| 产品名称 | 胀紧联结套 . (N.m) |
| 公司名称 | 青岛佳尔利机械有限公司 |
| 价格 | .00/个 |
| 规格参数 | 公称转矩.: (N.m) 轴孔.: 型号:Z8胀紧联接套 |
| 公司地址 | 山东省青岛市黄岛区东岳中路西端 |
| 联系电话 | 13792848558 15865551169 |

产品详情

公称转矩
型号

. (N.m)
Z8胀紧联接套

轴孔

| 基本尺寸 | | | | | | 内六角螺钉 | 额定负荷 | | 胀套与轴 | 胀套与轮 | 螺钉的 | 重量kg | |
|------|-----|----|----|----|----|----------|------|-----------------|-------------------|------------------------------------|--------------------------------------|------|--------------------|
| d | d | l1 | l2 | l3 | l4 | d1 | n | 轴向 力f1k n | 转矩m 1kn · m | 结合面上 的压力pf n/mm ² | 毂结合面 上的压力 pf n/mm ² | | 拧紧力 矩man · m |
| mm | | | | | | | | | | | | | |
| 20 | 47 | 17 | 22 | 28 | 34 | m6 × 20 | 5 | 30 | 0.29 | 220 | 95 | 17 | 0.25 |
| 22 | 47 | 17 | 22 | 28 | 34 | m6 × 20 | 5 | 30 | 0.32 | 200 | 95 | | 0.25 |
| 24 | 50 | 17 | 22 | 28 | 34 | m6 × 20 | 5 | 30 | 0.37 | 200 | 95 | | 0.27 |
| 25 | 50 | 17 | 22 | 28 | 34 | m6 × 20 | 6 | 36 | 0.45 | 215 | 110 | | 0.27 |
| 28 | 55 | 17 | 22 | 28 | 34 | m6 × 20 | 6 | 36 | 0.50 | 200 | 100 | | 0.32 |
| 30 | 55 | 17 | 22 | 28 | 34 | m6 × 20 | 6 | 36 | 0.54 | 190 | 100 | | 0.35 |
| 32 | 60 | 17 | 22 | 28 | 34 | m6 × 20 | 8 | 48 | 0.77 | 215 | 115 | | 0.37 |
| 35 | 60 | 17 | 22 | 28 | 34 | m6 × 20 | 8 | 48 | 0.84 | 190 | 110 | | 0.34 |
| 38 | 65 | 17 | 22 | 28 | 34 | m6 × 20 | 8 | 48 | 0.91 | 195 | 115 | | 0.40 |
| 40 | 65 | 17 | 22 | 28 | 34 | m6 × 20 | 8 | 48 | 0.96 | 190 | 105 | | 0.38 |
| 45 | 75 | 20 | 25 | 33 | 41 | m8 × 25 | 7 | 77 | 1.75 | 230 | 135 | 41 | 0.63 |
| 50 | 80 | 20 | 25 | 33 | 41 | m8 × 25 | 7 | 77 | 1.93 | 210 | 130 | | 0.68 |
| 55 | 85 | 20 | 25 | 33 | 41 | m8 × 25 | 8 | 88 | 2.45 | 215 | 135 | | 0.73 |
| 60 | 90 | 20 | 25 | 33 | 41 | m8 × 25 | 8 | 88 | 2.70 | 190 | 125 | | 0.78 |
| 63 | 95 | 20 | 25 | 33 | 41 | m8 × 25 | 9 | 100 | 3.18 | 205 | 140 | | 0.89 |
| 65 | 95 | 20 | 25 | 28 | 41 | m8 × 25 | 9 | 100 | 3.25 | 200 | 135 | | 0.83 |
| 70 | 110 | 24 | 30 | 40 | 50 | m10 × 30 | 8 | 141 | 5.00 | 220 | 140 | 83 | 1.33 |

| | | | | | | | | | | | | | |
|-----|-----|----|----|-----|-----|----------|----|------|-------|-----|-----|-----|-------|
| 75 | 115 | 24 | 30 | 40 | 50 | m10 × 30 | 8 | 141 | 5.25 | 200 | 130 | | 1.40 |
| 80 | 120 | 24 | 30 | 40 | 50 | m10 × 30 | 8 | 141 | 5.60 | 190 | 125 | | 1.48 |
| 85 | 125 | 24 | 30 | 40 | 50 | m10 × 30 | 9 | 159 | 6.75 | 200 | 135 | | 1.55 |
| 90 | 130 | 24 | 30 | 40 | 50 | m10 × 30 | 9 | 159 | 7.10 | 190 | 130 | | 1.63 |
| 95 | 135 | 24 | 30 | 40 | 50 | m10 × 30 | 10 | 176 | 8.35 | 200 | 140 | | 1.70 |
| 100 | 145 | 26 | 32 | 44 | 56 | m12 × 30 | 8 | 205 | 10.30 | 210 | 145 | 145 | 2.60 |
| 110 | 155 | 26 | 32 | 44 | 56 | m12 × 30 | 8 | 205 | 11.25 | 190 | 135 | | 2.80 |
| 120 | 165 | 26 | 32 | 44 | 56 | m12 × 30 | 9 | 231 | 13.9 | 210 | 145 | | 3.00 |
| 130 | 180 | 34 | 40 | 52 | 64 | m12 × 30 | 12 | 308 | 20.00 | 190 | 140 | | 4.60 |
| 140 | 190 | 34 | 40 | 54 | 68 | m14 × 40 | 9 | 317 | 22.25 | 180 | 130 | 230 | 4.90 |
| 150 | 200 | 34 | 40 | 54 | 68 | m14 × 40 | 10 | 352 | 26.3 | 190 | 140 | | 5.20 |
| 160 | 210 | 34 | 40 | 54 | 68 | m14 × 40 | 11 | 287 | 31.0 | 190 | 145 | | 5.50 |
| 170 | 225 | 44 | 40 | 64 | 78 | m14 × 40 | 12 | 422 | 35.9 | 150 | 115 | | 7.75 |
| 180 | 235 | 44 | 50 | 64 | 78 | m14 × 40 | 12 | 422 | 38.0 | 145 | 110 | | 8.15 |
| 190 | 250 | 44 | 50 | 64 | 78 | m14 × 40 | 15 | 528 | 50.1 | 170 | 130 | | 9.50 |
| 200 | 260 | 44 | 50 | 64 | 78 | m14 × 40 | 15 | 528 | 52.8 | 160 | 125 | | 9.90 |
| 220 | 285 | 50 | 56 | 72 | 88 | m16 × 40 | 12 | 587 | 64.5 | 145 | 110 | 355 | 13.40 |
| 240 | 305 | 50 | 56 | 72 | 88 | m16 × 40 | 15 | 734 | 88 | 165 | 130 | | 14.30 |
| 260 | 325 | 50 | 56 | 72 | 88 | m16 × 40 | 18 | 880 | 114 | 180 | 145 | | 15.50 |
| 280 | 355 | 60 | 66 | 84 | 102 | m18 × 50 | 16 | 948 | 132 | 150 | 120 | 485 | 22.90 |
| 300 | 375 | 60 | 66 | 84 | 102 | m18 × 50 | 18 | 1059 | 159 | 160 | 125 | | 24.40 |
| 320 | 405 | 74 | 81 | 101 | 121 | m20 × 50 | 18 | 1374 | 220 | 150 | 120 | 690 | 36.10 |
| 340 | 425 | 74 | 81 | 101 | 121 | m20 × 50 | 21 | 1603 | 272.5 | 175 | 135 | | 38.40 |
| 360 | 455 | 86 | 94 | 116 | 138 | m22 × 60 | 18 | 1710 | 308 | 140 | 110 | 930 | 46.20 |
| 380 | 475 | 86 | 94 | 116 | 138 | m22 × 60 | 21 | 1995 | 379 | 155 | 125 | | 55.00 |
| 400 | 495 | 86 | 94 | 116 | 138 | m22 × 60 | 21 | 1995 | 399 | 150 | 120 | | 61.00 |

注：z8型胀紧联结套螺钉的机械性能等级为12.9级。