

桥梁防撞墙定型模具基本说明

产品名称	桥梁防撞墙定型模具基本说明
公司名称	河北宏旭模具制造有限公司
价格	100.00/套
规格参数	模具材质:钢模具 主要加工设备:电焊机 运输方式:物流
公司地址	河北省保定市莲池区东金庄乡后辛庄村
联系电话	15720001423 15720001423

产品详情

桥梁防撞墙定型模具是连接防撞墙、防撞护栏所制作的，起到过渡的作用，作为防撞墙的端头端尾所制作，提醒车辆要进入有防撞墙的道路，要有序的进行行驶，与防撞墙的作用是相同的，起到保护行人以及车辆的作用。在制作的时候选择两块相同的钢板进行连接，连接的时候使用的是螺丝与拉杆搭配进行使用，可以有效的调节混凝土的壁厚，方便与其他模板进行连接，长度一般在80-200厘米之间，高度的话在80-150厘米之间，也会有更大的尺寸进行模板的制作，外侧会搭配筋板进行使用，使模板更加的坚固，不会出现破损、变形的情况，具体的尺寸以及筋板的数量要根据客户的需求进行具体的制作。

模具现浇的制作方式，将模具放置在所需位置，调节拉杆长度使所有使用模具的宽度一致。然后使用电动扳手将每节模具间的螺丝拧紧，检查各节模具间是否紧密连接，以防止灌浆后漏浆影响防护墙钢模板的质量。接下来，用混凝土搅拌车将混凝土搅拌均匀，隔段注入模具内，再用震动棒充分震动，以免产生气泡影响防护墙的坚固性。模板的使用不仅提高了施工效率，降低了成本，还为桥梁防护提供了强有力的支持

生产完之后需要把模具清洗一遍，在进行保存，模具的原材料使用的是钢板，钢模具的好处就是非常的耐用，能够使用2000次以上，使用模具的时候需要注意，不要让模具损坏掉，以免模具的使用时间受到一定的影响，模具也不能在湿润的环境下进行使用。水泥桥梁防撞墙模具制作速度非常快，加工出来的防撞墙不仅耐用，而且使用寿命长，是桥梁工程建设中的重要安全设施之一。

After production, the mold needs to be cleaned once and stored. The raw material of the mold is steel plate. The advantage of steel molds is that they are very durable and can be used more than 2000 times. When using the mold, it is necessary to be careful not to damage it, so as not to affect the use time of the mold. The mold cannot be used in a humid environment.