

FWP-350A 700V

产品名称	FWP-350A 700V
公司名称	苏州柏幕电气有限公司
价格	面议
规格参数	品牌:COOPER BUSSMANN (EATON ' S) 型号:FWP-350A
公司地址	苏州市长吴路1号
联系电话	18120071137

产品详情

North American — FWP 700V: 5-1200A North American style stud-mount fuses

Description: North American style stud-mount fuses.

Ratings: Volts: 700Vac/dc Amps: 5-1200A IR: 200kA RMS Sym. 50kA @700Vdc

Agency Information: CE, UL Recognition & CSA Component Acceptance on 5-800A

Features and Benefits • Excellent DC performance • Low arc voltage and low energy let-through (I2t) • Superior cycling capability

Typical Applications • DC common bus • DC drives • Power converters/rectifiers • Reduced voltage starters

Dimensions (in)

Order #	Fig.	A	B	C	D	E	F	G	H	J
FWP-5B-30B	1	2.87	0.563	1.855	2.477	2.477	0.25	0.405	0.063	0.25
FWP-35B-60B	1	4.375	0.813	2.75	3.708	3.312	0.344	0.725	0.125	0.542
FWP-70B-100B	1	4.406	0.947	2.594	3.625	3.563	0.344	0.75	0.125	0.375
FWP-125A-200A	1	5.09	1.5	2.84	4.19	3.5	0.41	1	0.25	0.75
FWP-225A-400A	1	5.09	2	2.84	4.28	3.53	0.41	1.5	0.25	0.78

FWP-450A-600A	1	7.09	2.5	2.84	5.72	4.19	0.53	2	0.38	1.3
FWP-700A-800A	1	6.63	2	2.844	5.562	5.062	0.625	1.5	0.25	0.875
FWP-900A-1000A	2	See Drawing								
FWP-1200A	3									

Catalog Numbers



Type	Electrical Characteristics				Ordering Information			Dimensions
	Rated Current RMS-Amps	I _{2t} (A ² Sec) Pre-arc	Clearing at 700V	Watts Loss	Part Number	Carton Qty.	Carton Weight (lbs)	Figure Number
FWP 700V	5A	1.6	10	1.5	FWP-5B	10	2.25	Fig.1
	10A	3.6	20	4	FWP-10B			
	15A	10	75	5.5	FWP-15B			
	20A	26	180	6	FWP-20B			
	25A	44	340	7	FWP-25B			
	30A	58	450	9	FWP-30B			
	35A	34	160	12	FWP-35B	5	1.21	
	40A	76	320	12	FWP-40B			
	50A	135	600	12	FWP-50B			
	60A	210	950	15.5	FWP-60B			
	70A	305	2000	18	FWP-70B	1	0.24	
	80A	360	2400	21	FWP-80B			
	90A	415	2700	25	FWP-90B			
	100A	540	3500	27	FWP-100B			
	125A	1800	7300	28	FWP-125A		0.65	
	150A	2900	11700	32	FWP-150A			
	175A	4200	16700	35	FWP-175A			
	200A	5500	22000	43	FWP-200A			
	225A	7700	31300	45	FWP-225A		1.17	
	250A	10500	42500	48	FWP-250A			
300A	17600	71200	58	FWP-300A				
350A	23700	95600	65	FWP-350A				
400A	31000	125000	78	FWP-400A				
450A	36400	137000	94	FWP-450A		2.39		
500A	45200	170000	107	FWP-500A				

600A	66700	250000	122	FWP-600A		
700A	54000	300000	125	FWP-700A	1.21	
800A	78000	450000	140	FWP-800A		
900A	91500	530000	150	FWP-900A	6.6	Fig.2
1000A	120000	600000	170	FWP-1000 A		
1200A	195000	1100000	190	FWP-1200 A		Fig.3

- 1 kg = 2.2 lbs 1 lb = 0.45 kg - Interrupting rating 200kA RMS Symmetrical. - Watts loss provided at rated current. - (700 Vdc/Interrupting rating 50kA) U.L. Recognition & CSA Component Acceptance on 5 through 100 & 700 through 800 amperes. - (700 Vdc/Interrupting rating 10kA) U.L. Recognition & CSA Component Acceptance on 125 through 600 amperes.