

三端口高功率环形器

产品名称	三端口高功率环形器
公司名称	上海量青光电技术有限公司
价格	1.00/个
规格参数	品牌:量青光电 型号:环形器 激光器:放大器
公司地址	上海市奉贤区奉城镇东街98号13幢1176室(注册地址)
联系电话	021-64778883 17317628715

产品详情

三端口高功率偏振无关光环行器

3 Port High Power Polarization Insensitive Optical Circulator

PDF资料下载

Applications:	Features:
EDFA,DWDM and OTDR DWDM and OADM networks Bi-directional transmission system	High isolation & High Return Loss Low insertion loss & PDL Optical Path Epoxy Free

Parameter	Unit	Specification	
Part No.	-	LQ-HPCIR-W-PW-P-PF-C	
Operating wavelength	nm	1550+/-30	C+L band(1520~1620)

Peak Isolation @23?	dB	>45	40
Isolation@23?	dB	>35	>30
Insertion Loss@23?	dB	?1.0	?1.0
Insertion Loss@0~70?	dB	<1.2	1.2
PDL	dB	<0.15	<0.20
Power handling CW	mW	1,2,3,5	
Return loss	dB	>50	
Fiber type	-	SMF-28e	
PMD	ps	<0.1	
Directivity	-	>50	
Operating Temperature	°C	0~+70	
Storage Temperature	°C	-40~+85	
Dimensions	mm	?5.5 × L50 or L90*W20*H9.5(ABS)	

Above specifications are for device without connector.

For devices with connector,IL will be 0.3dB higher,ER will be 2dB lower and RL will be 5dB lower, and max handling power is 1W

The PM fiber and the connector key are aligned to the slow axis.

--	--	--	--	--

联系人: Michael 李 (欢迎来电)
公司电话: 021-64778883 (欢迎咨询)