

1310,1480,1550保偏光隔离器

产品名称	1310,1480,1550保偏光隔离器
公司名称	上海量青光电技术有限公司
价格	10000.00/个
规格参数	品牌:量青光电 型号:光隔离器 SLD光源:衰减器
公司地址	上海市奉贤区奉城镇东街98号13幢1176室(注册地址)
联系电话	021-64778883 17317628715

产品详情

1310,1480,1550nm高功率保偏光隔离器(1-20w)

1310, 1550nm High Power PM Isolator (1-20w)

Applications:		Features:	
EDFA Fiber Laser		Low Insertion Loss & PDL High Isolation & ReturnLoss High reliability	
Parameter		Specification	
Part No.	-	LQ-HPIPI/HPIPS-W-PT-PW-T-PF-C	
Type.	-	Single Grade	Dual Grade
Operating wavelength	nm	1310,1480,1550	

Bandwidth	nm		±20
Peak isolation	dB	42	58
Isolation@23?	dB	>28	>48
Insertion Loss@23?	dB	?0.5(Typ 0.35)	?0.55 (Typ 0.4)
ER Type B (Both axis working)	dB	>22	>22
ER Type F (Fast axis blocked)	dB	>23	>23
Power handling CW	mW	1,2,3,5,10,20	
Return loss	dB	>50	
Fiber type PANDA Fiber	-	PM1310,PM1550	
Operating Temperature	°C	-5~+70	
Storage Temperature	°C	-40~+85	
Dimensions	mm	?5.5 × L35	

Above specifications are for device without connector. For devices with connector,IL will be 0.3dB higher,ER 2dB lower and RL will be 5dB lower, and max handling power is 1W The PM fiber and the connector key are aligned to the slow axis.

???????

??????

???????

850,980,1064???????

??????

????????????????TOSA, ROSA, BOSA

联系人: Michael 李 (欢迎来电)
公司电话: 024-64778883 (欢迎咨询)