

DDU全自动装盒机 插座装盒机 继电器装盒机

产品名称	DDU全自动装盒机 插座装盒机 继电器装盒机
公司名称	广州大度机械科技有限公司
价格	220000.00/台
规格参数	品牌:DDU 型号:120
公司地址	广州市增城区新塘镇牛仔城兴派产业园二巷1号
联系电话	18022885838 18022885838

产品详情

DDU全自动插座装盒机 继电器装盒机 充电器装盒机有：

高速装盒机，立式装盒机，连续式装盒机，卧式装盒机，间隙式装盒机

DDU全自动插座装盒机 继电器装盒机 充电器装盒机主要性能结构特点：

采用自动送料、开盒、入盒、打批号、封盒、剔废等的包装形式，结构紧凑合理，操作调整简单；

采用伺服/步进电机和触摸屏、PLC可编程控制系统，人机界面显示操作更清晰简便，自动化程度高，更具人性化；

采用光电眼自动检测跟踪系统，空包不下盒，最大限度地节约了包装材料；

包装范围大，调节方便，各种规格尺寸之间可实现快速转换；

更换规格无需更换模具，只需调节即可实现；

采用物品进盒不到位自动停机和主传动电机过载保护装置，适用更安全可靠；

可根据客户要求，采用上翻式安全防护罩，操作简便，外形美观。

可与瓶装线、灌装机、贴标机、喷码机、在线称量仪、三维包装机、其它生产线等设备实现联动生产；

可根据包装物要求设计各种自动下料器和入盒系统；

10、可根据客户要求选配热熔胶机，采用热熔胶喷胶封盒。

Main performances and structure features:

1. Packing forms such as automatic feeding, box opening, boxing, batch No. printing, box sealing, waste rejecting, etc. are adopted. Featured by compact and reasonable structure, simple operation and adjustment.
2. Servo/step motor, touch screen, PLC control system and man-machine interface display make operation more clear and convenient. With high automation degree, the machine is more user-friendly.
3. The photoelectric eye automatic detection tracking system is adopted. No boxing is made if the bag is empty, so as to save packing materials to the utmost extent.
4. With wide packing range and convenient adjustment, fast switching among various specifications and sizes can be realized.
5. Change of specifications does not need change of molds, but can be realized through adjustment.
6. Automatic stopping is available when the material boxing is not in place, and the main driving motor overload protection device is used, so that the machine is safer and more reliable.
7. According to customer requirements, the upturning type safety protective cover is adopted, which is featured by simple operation and beautiful appearance.
8. Linked production with the bottling line, filling machine, labeling machine, ink jet printer, online weightometer, three-dimensional packing machine and other production lines and equipment can be realized.
9. Various automatic feeders and boxing systems can be designed according to different requirements of packing materials.
10. According to customer requirements, the hot melt glue machine can be equipped, and the hot melt glue spreading and box sealing and mechanical glue brushing and box sealing can be adopted.

DDU全自动插座装盒机 继电器装盒机 充电器装盒机主要性能技术参数：

项目/型号Item/model	DDU-120
包装速度Packing speed	30-120盒/分钟boxes/minute
纸盒尺寸范围 Size range of carton	L (60-200) mm × W (20-80) mm × H (15-60) mm

纸盒纸质要求 Paper quality of carton		250-300g/m ³
说明书尺寸范围 Size range of use instructions		L (100-260) mm × W (100-190) mm
说明书纸质要求 Paper quality of use instructions		55-70 g/m ³
电机功率Motor power		1.5KW
电源类型Power supply type		三相四线380V 50Hz Three-phase four-wire 380V 50Hz
机器噪音Machine noise		80dB
气源Air supply		0.5-0.7 Mpa
耗气量Air consumption		120-160L/min
外形尺寸Outline dimensions	主机部分	L3100 × W1200 × H1900 mm
	理瓶部分	L1800 × W900 × H1000 mm
整机重量Machine weight		1200Kg

注：本公司产品更新换代较快，若有变动请按实物为准，恕不另行通知！