

# 美标球阀 美标金属硬密封球阀

产品名称	美标球阀 美标金属硬密封球阀
公司名称	上海凯祥阀门有限公司
价格	1100.00/台
规格参数	品牌:凯祥阀门 型号:Q41F/H-150LB
公司地址	上海市金山区卫昌路251号3幢1458室
联系电话	021-51870907 13585628232

## 产品详情

产品说明：

一、产品[美标球阀]的详细资料：

产品型号：Q41F/H-150LB

产品名称：美标球阀 美标金属硬密封球阀

产品特点：美标软密封浮动球阀,日标软密封浮动球阀,浮动球阀

二、产品性能规范：

公称压力 (PN)	1.6	2.5	4.0	6.4
壳体试验压力	2.4	3.8	6.0	9.6
密封试验 (液)	1.8	25.8	4.4	7.0
密封试验 (气)	0.5~0.7			
适用介质	C P R 水、油品、蒸汽 硝酸类 醋酸类			
适用温度	200			



H	mm	59	63	75	97	107	142	152	178	252
W	mm	130	130	160	230	230	400	400	700	1100
重量	kg	2.5	3.5	5.5	10.5	14.5	23.5	30.0	55.0	81.0

六、上海凯祥阀门美标金属硬密封球阀150Lb外形尺寸和连尺寸：

公称通径		单位	L	D	T	G	C	n-
in	mm							
1/2	15	mm	108	89	12	35	60.5	4-15
		in	4.25	3.5	0.47	1.38	2.38	4-0.5
3/4	20	mm	117	98	12	43	70	4-15
		in	4.61	3.86	0.47	2	3.13	4-0.5
1	25	mm	127	108	12	51	79.5	4-15
		in	5	4.25	0.47	2	3.13	4-0.5
1-1/2	40	mm	165	127	14.3	73	89.5	4-16
		in	6.5	5	0.56	2.88	3.88	4-0.6
2	50	mm	178	152	15.9	92	120.5	4-19
		in	7	6.00	0.625	3.62	4.75	4-0.7
2-1/2	65	mm	190	178	17.5	105	139.5	4-19
		in	7.5	7	0.69	1.12	5.50	4-0.7
3	80	mm	203	190	19.1	127	152.4	4-19
		in	8	7.50	0.75	5	6	4-0.7
4	100	mm	229	229	23.9	157	190.5	4-19
		in	9	9	0.94	6.19	7.5	4-0.7
6	150	mm	394	279	26	216	241.5	8-22
		in	15.5	10.98	1.02	8.5	9.50	8-0.8
8	200	mm	457	343	29	270	298.5	8-22

		in	18.00	13.50	1.12	10.62	11.75	8-0.8
10	250	mm	533	406	31	324	362	12-24
		in	20.98	16	1.2	12.75	14.75	12-1
12	300	mm	610	483	32	381	432	12-24
		in	24	19	1.26	15	17	12-1

七、上海凯祥阀门美标金属硬密封球阀300Lb外形尺寸和连接尺寸：

公称通径		单位	L	D	T	G	C	n-
in	mm							
1/2	15	mm	140	95	15	35	66.5	4-15
		in	5.51	3.74	0.59	1.38	2.62	4-0.5
3/4	20	mm	152	117	16	43	82.5	4-19
		in	5.98	4.61	0.62	1.69	3.25	4-0.7
1	25	mm	165	124	18	51	89	4-19
		in	6.5	4.9	0.71	2	3.5	4-0.7
1-1/2	40	mm	190	156	20.7	73	114.5	4-22
		in	7.5	6.12	0.81	2.88	4.51	4-0.8
2	50	mm	216	165	22.3	92	127	8-19
		in	8.5	6.5	0.88	3.62	5	8-0.7
2-1/2	65	mm	241	190	25.4	105	149	8-22
		in	9.5	7.5	1	4.12	5.87	8-0.8
3	80	mm	283	210	28.5	127	168.5	8-22
		in	11.25	8.25	1.12	5	6.62	8-0.8
4	100	mm	305	254	31.8	157	200	8-22
		in	12	10	1.25	6.19	7.88	8-0.8

6	150	mm	403	318	36.6	216	270	12-2
		in	15.875	12.5	1.44	8.5	10.62	12-0.8
8	200	mm	502	381	42	270	330	12-2
		in	19.76	15	16.5	10.62	12.99	12-1
10	250	mm	568	444	48	324	387.5	16-2
		in	22.36	17.50	1.89	12.75	15.25	16-1.1

<a href="#">浮球阀</a>	<a href="#">美标球阀</a>	<a href="#">法兰球阀</a>	<a href="#">电动球阀</a>	<a href="#">气动球阀</a>	<a href="#">保温球阀</a>
<a href="#">高压球阀</a>	<a href="#">四通球阀</a>	<a href="#">陶瓷球阀</a>	<a href="#">高温球阀</a>	<a href="#">低温球阀</a>	<a href="#">抗硫球阀</a>
<a href="#">衬氟球阀</a>	<a href="#">放料球阀</a>	<a href="#">三通球阀</a>	<a href="#">轨道球阀</a>	<a href="#">弹簧球阀</a>	<a href="#">氨用球阀</a>
<a href="#">塑料球阀</a>	<a href="#">V型球阀</a>	<a href="#">斜面球阀</a>	<a href="#">真空球阀</a>	<a href="#">双联球阀</a>	<a href="#">天然球阀</a>
<a href="#">固定式球阀</a>	<a href="#">卫生级球阀</a>	<a href="#">内螺纹球阀</a>	<a href="#">喷煤粉球阀</a>	<a href="#">焊接式球阀</a>	<a href="#">偏心半球阀</a>
<a href="#">铝合金球阀</a>	<a href="#">长输管线球阀</a>	<a href="#">焦炉专用球阀</a>	<a href="#">蜗轮传动球阀</a>	<a href="#">金属硬密封球阀</a>	<a href="#">上海凯祥球阀</a>