

HDYG03-----全自动中小型轴承压盖机

产品名称	HDYG03-----全自动中小型轴承压盖机
公司名称	无锡市惠荣自动化科技有限公司
价格	.00/1
规格参数	品牌:惠荣 型号:HDYG03-
公司地址	无锡滨湖区梅园徐巷449号
联系电话	0510-85200718 13961888421

产品详情

HDYG03-----全自动中小型轴承压盖机

?????

1? ??????ø62mm-ø90mm?????????????

2? ?????????????????????2?????????????????

3? ?????????????????NG?????

4? ??????????????????????

5? ??????????????????---?????---?????--- ??---?????????????????---?????---?????---NG??---??---?????????

6? ??????????7?????????????????????????????????

?????

1? ??????????????????????????????????????????

2? ?????????????????????????????????????????

????????????????

3? ??????3?5????????????????????????????

????????????????

4? ?????????????????

?????NG??????

5? ??????????1.3?????

????????????????

6? ?????????????????

????????????????

?????

??????

ø62-ø90mm

????

?1.6?/?

????

????????????

?????

????????

????

?????

??

220V 50HZ 5A

?? 0.4MPa

???? 1300×650×1600

?? ?300KG

????????????????? ????0510-85200718 ????0510-85200728

WuXi HuiRong Automation Technology Co., Ltd. ???www.huirongat.com ???huirongat@163.com

HDYG03 -----

Auto small and medium bearing capping machine

Major functions?

1? Applicable for double-sided dust cap press with an external bearing diameter of $\varnothing 62\text{mm}$ - $\varnothing 90\text{mm}$.

2? Two manufacturing modes-- cover both sides, gland, plastic sealed cap and iron dust cap, switching through procedures.

3? NG products such as gland inspection function, no cap and height of cap etc, can be removed.

4? Grease evenly distribution function, free time setting.

5? Manufacturing procedures: put cap on the first side(or press plastic cap)-- press iron caps tightly--gland inspection--turn over--put cap on the second side-(or press plastic cap)--press iron caps tightly--gland inspection--NG ejection--even distribution of grease--qualified products being finished

6? Intelligent operating system, 7 inches true color touching screen , parameters and states information display at the same time, clear at a glance, easy to operate.

Structural features?

1? Together with loading plates, the machine can be used separately as well as connecting at the back of automatic greasing machine to achieve attachment production.

2? Linear slide rail cover delivery platform, accuracy and smoothness in delivering, no block in cap and adjustable in the gaps between guide mechanism and the platform. Plastic cover gaskets are also cut more smoothly.

3? 3 ton or 5 tons punching strength of gas liquid cylinder dust cap, double guiding- pillar stamping structure, stress equilibrium in gland and adjustable in depth

4? Electrical contact method to check height of cover, easy and reliable, eliminating NG products automatically.

5? The most stable equipment among the same kind of equipment industry with a highest processing efficiency reaching around 1.3 seconds.

6? All components using best quality configurations to ensure long term working stability of equipments.

Technical parameters?

Applicable range	ø62-ø90mm
Working efficiency	1.6 seconds for one piece
Bearing loading mode	Automatic line or loading tray
Stamping cover method	Gas-liquid boosting cylinder stamping

Power 220V 50Hz 5A

Air source 0.4MPa

External dimensions 1300×650×1700mm

Weight 400kg

????????????????? ???0510-85200718 ???0510-85200728

WuXi HuiRong Automation Technology Co., Ltd. ???www.huirongat.com ???huirongat@163.com